

Product data sheet

Specifications



APC Smart-UPS Modular Ultra On-Line, 10kW scalable to 15kW, Lithium-ion, Tower 24U, 208/240V, Network Management, W/ External battery chassis

SRYL10K15XLT24

Overview

Lead Time Usually in Stock

Main

Main Input Voltage 208 V AC

Product Or Component Type Uninterruptible power supply (UPS)

Other Input Voltage 240 V

Main Output Voltage 120 V AC

Other Output Voltage 240 V

Kw Rating 10000 W

Rated Power In Va 10000 VA

Battery Type Li-Ion (Lithium Ion)

Batteries & Runtime

Run Time [View Runtime Graph](#)

Efficiency [View Efficiency Graph](#)

Included Battery Modules 2

Rbc Quantity 2

Battery Design Life 8...10 year(s)

General

Product Web Sub-Family Network management card

Number Of Power Module 2

Number Preinstalled Power Module 2

Physical

Color Black and silver

Height 47.17 in (1198 mm)

Width 23.62 in (600 mm)

Depth 35.43 in (900 mm)

Net Weight 427.70 lb(US) (194 kg)

Mounting Location Front

Input

Input Frequency	40 - 70 Hz
Number Of Input Connectors	1 Hard Wire 4-wire (2PH+N+G)
Maximum Input Current Per Phase	51 A
Load Power Factor	0.5 leading to 0.5 lagging

Output

Topology	Double Conversion Online
Waveform Type	Sine wave
Overload Operation	60 seconds @ 125% and 30 seconds @ 150%
Bypass Type	Built-in Bypass
Maximum Configurable Power In Va	15000 VA

Conformance

Product Certifications	ENERGY STAR V2.0 (USA)
------------------------	------------------------

Environmental

Ambient Air Temperature For Operation	32...104 °F (0...40 °C)
Operating Altitude	0...9842.52 ft (0...3000 m)
Ambient Air Temperature For Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 %
Storage Altitude	0.00...49212.60 ft (0...15000 m)
Acoustic Level	68 dB

Communications & Management

Pre-Installed Smartslot™ Cards	Network management card
Control Panel	Touch Screen LCD User Interface
Emergency Power Off (Epo)	Yes

Ordering and shipping details

Gtin	731304622116
Country Of Origin	PH

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	52.05 in (132.2 cm)
Package 1 Width	29.37 in (74.6 cm)
Package 1 Length	39.17 in (99.5 cm)
Package 1 Weight	476.99 lb(US) (216.36 kg)

Contractual warranty

Warranty


5 YR


Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

[Learn more about Green Premium >](#)

Well-being performance

 Mercury Free

 Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive Compliant with Exemptions

China Rohs Regulation [China RoHS declaration](#)
Product out of China RoHS scope. Substance declaration for your information.
