



## MS725dvn

Reliability. Security. Productivity.



MS725dvn



This is a Class A device according to international electromagnetic emissions standards (i.e., FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.

# Lexmark MS725dvn

The Lexmark MS725dvn reliably prints in a wide range of sizes on diverse materials, from small, narrow-format papers to vinyl outdoor media. Its ease of use, robust media handling and full-spectrum security all complement its comprehensive connectivity options and up-to 55-page-per-minute output\*.



## Get more done

- ▶ Take advantage of a wide range of sizes and diverse materials—from small, narrow-format papers to vinyl outdoor media.
- ▶ Powerful 1-GHz dual-core processor and 512 MB memory drives printing at up to 55 ppm.\*
- ▶ Robust paper handling includes reliable feeding of a wide range of media types and sizes, up to 4,400 sheets of standard input and optional finishing
- ▶ Connect via Ethernet, USB, or simple mobile printing options.

## Interact with ease

- ▶ 2.4-inch/6-cm colour LCD lets you configure, interact and monitor vital system information.
- ▶ Front access to the paper path and power button means you'll virtually never have to access the back of the device, allowing placement in or on cabinets.
- ▶ Innovative serviceability features, starting with single-door access to parts and supplies, help you resolve problems quickly.

## Ready when you are

- ▶ Long-life fuser and imaging components extend uptime.
- ▶ Unison™ Toner replacement cartridges deliver up to 55,000 pages\*\* of high-quality printing.
- ▶ Steel frame and durable design stands up to heavy use and harsh environments.

## Full-spectrum security

- ▶ Lexmark's full-spectrum security architecture helps keep your information safe—in the document, on the device and over the network.



## Built for planet earth

- ▶ Energy management features reduce power consumption in active use or sleep mode.
- ▶ Standard two-sided printing saves paper.
- ▶ Recycle cartridges through the award-winning Lexmark Cartridge Collection Program (LCCP).

\*Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds).  
\*\*Average standard page yield value declared in accordance with ISO/IEC 19752.

# Lexmark MS725dvn



- 1 **Printer with 2.4-inch (6 cm) display**  
17.5 x 16.85 x 20.1 inches  
445 x 428 x 510 mm
- 2 **100-sheet multipurpose feeder**  
Dimensions included as part of base model
- 3 **550-sheet tray**  
Dimensions included as part of base model
- 4 **550-sheet tray**  
4.3 x 16.85 x 20.1 inches  
110 x 428 x 510 mm
- 5 **2100-sheet tray**  
13.8 x 16.85 x 20.1 inches  
350 x 428 x 510 mm
- 6 **Caster base**  
5 x 20.5 x 27.3 inches  
126 x 521 x 693 mm

- 7 **Staple, hole punch finisher**  
10.3 x 18.2 x 20.0 inches  
263 x 462 x 507 mm
- 8 **Staple finisher**  
9.7 x 17.1 x 16.3 inches  
246 x 435 x 414 mm
- 9 **Output expander**  
6.5 x 16.6 x 15.0 inches  
165 x 421 x 380 mm
- 10 **4-Bin mailbox**  
10.7 x 16.6 x 15.1 inches  
272 x 421 x 384 mm
- 11 **High-capacity output expander**  
12.2 x 16.6 x 13.2 inches  
310 x 421 x 335 mm
- 12 **250-sheet tray**  
3.2 x 16.85 x 20.1 inches  
80 x 428 x 510 mm

- 13 **550-sheet lockable tray**  
4.3 x 16.85 x 20.1 inches  
110 x 428 x 510 mm
- 14 **250-sheet lockable tray**  
3.2 x 16.85 x 20.1 inches  
80 x 428 x 510 mm
- 15 **Swivel cabinet**  
10.4 x 18.7 x 23.6 inches  
263 x 476 x 600 mm
- 16 **Adjustable printer stand**  
23 x 23.5 x 23.5  
584.2 x 596.9 x 596.9
- 17 **Spacer to add additional height**  
4.3 x 16.85 x 20.1 inches  
110 x 428 x 510 mm

Standard  
 Optional

Note 1: Supports up to four optional trays. For maximum paper input capacity, install three optional 550-sheet trays and one optional 2100-sheet tray. When a 2,100-sheet tray is installed, it must be the bottom tray, and a caster base is required.

Note 2: Supports many output configurations, including: Any combination of up to three output expanders and four-bin mailboxes; OR staple finisher with four-bin mailbox; OR staple finisher with output expander; OR output expander with high-capacity output expander; OR the staple, hole punch finisher; OR any single output option by itself. When installing the optional stapler, it must always be on top. When installing the optional high-capacity output expander, it must always be on the bottom.

Note 3: All measurements are shown as height x width x depth. For more information about supported configurations, refer to the Printer, Option and Stand Compatibility Guide at [http://www.lexmark.com/publications/furniture\\_safety/](http://www.lexmark.com/publications/furniture_safety/)

© 2019 Lexmark. All rights reserved.

Lexmark, the Lexmark logo and Unison are trademarks of Lexmark International, Inc., registered in the United States and/or other countries. AirPrint® and the AirPrint Logo® are trademarks of Apple, Inc. Google Cloud Print™ is a trademark of Google, Inc. MOPRIA®, the Mopria® Logo™ and the Mopria® Alliance logos are trademarks, service marks, and certification marks of Mopria Alliance, Inc. in the United States and other countries. All other trademarks are the property of their respective owners.® Alliance logos are trademarks, service marks, and certification marks of Mopria Alliance, Inc. in the United States and other countries. All other trademarks are the property of their respective owners.

This product includes software developed by the OpenSSL Project for use in the Open SSL Toolkit (<http://www.openssl.org/>).

## Product specifications

## Lexmark MS725dvn

### Printing

Display	2.4-inch (60 mm) Colour LCD display
Print Speed: Up to <sup>6</sup>	Black: 55 ppm
Time to First Page: As fast as	Black: 8 seconds
Print Resolution	Black: 1200 Image Quality, 1200 x 1200 dpi, 2400 Image Quality, 300 x 300 dpi, 600 x 600 dpi
Memory	Standard: 512 MB / Maximum: 4608 MB
Hard Disk	Option available
Recommended Monthly Page Volume <sup>2</sup>	5000 - 75000 pages
Maximum Monthly Duty Cycle: Up to <sup>3</sup>	300000 pages per month

### Supplies<sup>7</sup>

Laser Cartridge Yields (up to) <sup>1</sup>	7,500-page Cartridge, 15,000-page High Yield Cartridge, 35,000-page Extra High Yield Cartridge, 55,000-page Ultra High Yield Cartridge
Imaging Unit Estimated Yield: Up to	150000 pages, based on 3 average letter/A4-size pages per print job and ~ 5% coverage
Cartridge(s) Shipping with Product <sup>1</sup>	11,000-page Starter Return Program Toner Cartridge

### Paper Handling

Included Paper Handling	550-Sheet Input, 100-Sheet Multipurpose Feeder, 550-Sheet Output Bin, Integrated Duplex
Optional Paper Handling	250-Sheet Tray, 550-Sheet Tray, 2100-Sheet Tray, 250-Sheet Lockable Tray, 550-Sheet Lockable Tray, 4-Bin Mailbox, Staple Finisher, Staple Punch Finisher, High Capacity Output Expander, Output Expander
Paper Input Capacity: Up to	Standard: 650 pages 20 lb or 75 gsm bond / Maximum: 4400 pages 20 lb or 75 gsm bond
Paper Output Capacity: Up to	Standard: 550 pages 20 lb or 75 gsm bond / Maximum: 2550 pages 20 lb or 75 gsm bond
Media Types Supported	Card Stock, Dual Web Labels, Integrated Labels, Paper Labels, Plain Paper, Polyester Labels, Transparencies, Vinyl Labels, Refer to the Paper & Specialty Media Guide
Media Sizes Supported	A4, A5, Executive, Folio, JIS-B5, Legal, Letter, Statement, Universal, Oficio, A6

### General Information<sup>4</sup>

Standard Ports	One Internal Card Slot, USB 2.0 Specification Hi-Speed Certified (Type B), Gigabit Ethernet (10/100/1000), Front USB 2.0 Specification Hi-Speed Certified port (Type A)
Optional Network Ports / Optional Local Ports	Marknet N8370 WiFi Option, MarkNet N8230 Fiber Ethernet Print Server, Marknet N8372 WiFi Option / Internal RS-232C serial, Internal 1284-B Bidirectional Parallel
Noise Level: Operating	Print: 56 dBA
Specified Operating Environment	Humidity: 8 to 80% Relative Humidity, Temperature: 10 to 32°C (50 to 90°F), Altitude: 0 - 2896 Meters (9,500 Feet)
Limited Warranty - See Statement of Limited Warranty	1-Year Advanced Exchange, Next Business Day
Size (mm - H x W x D) / Weight	445 x 428 x 510 mm / 25.4 kg

All information in this brochure is subject to change without notice. Lexmark is not liable for any errors or omissions.

**This is a Class A device according to international electromagnetic emissions standards (i.e., FCC Rules, EN 55022/EN 55032, etc.). Class A products are intended for use in non-residential/non-domestic environments. Use of a Class A product in residential/domestic environments may cause interference to radio communications and require corrective measures.**

<sup>1</sup>Average continuous cartridge yield is stated number of standard pages as listed. Declared yield value in accordance with ISO/IEC 19798. <sup>2</sup>Recommended Monthly Page Volume<sup>2</sup> is a range of pages that helps customers evaluate Lexmark's product offerings based on the average number of pages customers plan to print on the device each month. Lexmark recommends that the number of pages per month be within the stated range for optimum device performance, based on factors including: supplies replacement intervals, paper loading intervals, speed, and typical customer usage. <sup>3</sup>Maximum Monthly Duty Cycle<sup>3</sup> is defined as the maximum number of pages a device could deliver in a month using a multishift operation. This metric provides a comparison of robustness in relation to other Lexmark printers and MFPs. <sup>4</sup>Printers are sold subject to certain license/agreement conditions. See [www.lexmark.com/printerlicense](http://www.lexmark.com/printerlicense) for details. <sup>5</sup>Actual Yield may vary based on other factors such as device speed, paper size and feed orientation, toner coverage, tray source, percentage of black-only printing and average print job complexity. <sup>6</sup>Print and copy speeds measured in accordance with ISO/IEC 24734 and ISO/IEC 24735 respectively (ESAT). For more information see: [www.lexmark.com/ISOspeeds](http://www.lexmark.com/ISOspeeds). <sup>7</sup>Product functions only with replacement cartridges designed for use in a specific geographical region. See [www.lexmark.com/regions](http://www.lexmark.com/regions) for more details.