

# 2010 SDR-T50 CAMCORDER



## **ADVANCED OPTICAL 78X ZOOM WITH O.I.S.**

Your image is stabilized all the way out with the longest zoom in the industry.

## **33mm WIDE ANGLE LENS**

New wider angle lens lets you fit even more of your subject into the video.



## **INTELLIGENT AUTO WITH AE/AF TRACKING**

Confidently record as the camcorder automatically adjusts settings.

- 4GB Built-In Memory
- Long Recording Mode
- Easy-to-Use YouTube™ Uploader
- 2.7" Wide LCD
- 1.9 Second Quick Power-On
- Wind Noise Canceller
- DVD Quality MPEG2 Recording

**Panasonic**®

# 2010 SDR-T50 Standard Definition Camcorder Specifications

|                                     |   | SDR-T50   |
|-------------------------------------|---|---|
| <b>GENERAL</b>                      |   |   |
| Power Supply (Battery / AC Adapter) |   | DC3.6V/5.0V   |
| Power Consumption                   |   | Max. 2.9W (Recording)/Max. 7.7W (Charging)  |
| Weight (w/o Battery)                |   | Approx. 213g (0.47lb.)  |
| Dimension (W x H x D)               |   | 54.9 x 64 x 107.3 [mm] (2.16 x 2.52 x 4.22 [inch])  |
| Media                               |   | Built-in memory (4GB), SD/SDHC/SDXC Memory Card   |
| On-Screen Display Language          |   | Please refer to "OSD" sheet   |
| <b>IMAGE SENSOR</b>                 |   |   |
| Image Sensor                        |   | 1/8" CCD  |
| Total Pixels                        |   | 0.8 megapixels  |
| Effective Pixels                    | Motion Image & Still Image  | 0.41 megapixels (Tele) – 0.52 megapixels (Wide) [4:3]<br>0.38 megapixels (Tele) – 0.47 megapixels (Wide) [16:9]   |
| <b>LENS SECTION</b>                 |   |   |
| Lens Brand                          |   | Panasonic Lens  |
| F Value                             |   | F1.9(Wide)/5.7(Tele)  |
| Zoom                                | Optical Zoom<br>Intelligent Zoom<br>Enhanced Optical Zoom<br>Digital Zoom | 70x<br>—<br>78x<br>100x/3500x (The maximum value of zoom magnification)   |
| Focal Length                        |   | 1.48–104mm  |
| 35mm Film camera Equivalent         |   | Enhanced Optical Zoom OFF: 37.4mm–2625mm [4:3], 36.5mm–2571mm [16:9]<br>Enhanced Optical Zoom ON: 33.5mm–2625mm [4:3], 32.8mm–2571mm [16:9]   |
| Filter Diameter                     |   | —   |
| <b>CAMERA SECTION</b>               |   |   |
| Standard Illumination               |   | 1400lx  |
| Minimum Illumination                |   | 5.0 lx (1/30 Low Light scan mode)<br>2 lx (Color Night Rec)   |
| Image Stabilizer                    |   | Advanced O.I.S. (Optical Image Stabilization)   |
| Focus                               |   | Auto/Manual   |
| White Balance                       |   | Auto/Indoor1/Indoor2/Sunny/Cloudy/White set   |
| Shutter Speed                       | Motion Image & Still Image  | Auto Slow Shutter ON: 1/30–1/8000<br>OFF: 1/60–1/8000   |
| Iris                                |   | Auto/Manual   |
| Backlight Compensation              |   | Yes   |
| <b>MONITOR</b>                      |   |   |
| EVF                                 |   | —   |
| Monitor (LCD)                       |   | 2.7" Wide LCD (123,200 dots)  |
| <b>STILL IMAGE SECTION</b>          |   |   |
| Recording Format                    |   | JPEG  |
| Recording Image Size                | Still Picture   | 0.3 megapixels (640 x 480) [4:3]<br>0.2 megapixels (640 x 360) [16:9]   |
|                                     | Simultaneous Recording<br>Creating still picture from motion picture      | 0.3 megapixels (640 x 480) [4:3], 0.2 megapixels (640 x 360) [16:9]<br>0.3 megapixels (640 x 480) [4:3], 0.2 megapixels (640 x 360) [16:9]  |
| Flash                               |   | —   |
| DPOF                                |   | Max. 999 images   |
| <b>RECORDING SECTION</b>            |   |   |
| Signal System                       |   | 525/60i   |
| Recording Format                    |   | MPEG2   |
| Recording Mode                      |   | XP (10Mbps/VBR), (704 x 480)<br>SP (5Mbps/VBR), (704 x 480)<br>LP (2.5Mbps/VBR), (704 x 480)<br>LXP (5Mbps/VBR), (704 x 480)<br>LSP (2.5Mbps/VBR), (704 x 480)<br>LLP (1.25Mbps/VBR), (704 x 480) |
| Audio Recording System              | XP / SP / LP<br>LXP / LSP / LLP   | Built-in memory, Dolby Digital (2ch)<br>SD Card; Dolby Digital (2ch), MPEG1 AudioLayer 2<br>Built-in memory/SD Card; AAC<br>Stereo mic/Zoom mic   |
| Microphone                          |   | Dynamic type  |
| Speaker                             |   | —   |
| Media Remaining Indication          |   | Yes   |
| <b>INTERFACES</b>                   |   |   |
| AV                                  |   | Out   |
| HDMI                                |   | —   |
| Microphones (stereo mini)           |   | —   |
| Headphone (stereo mini)             |   | —   |
| USB                                 |   | 2.0 Hi-Speed  |
| AV multi                            |   | —   |
| <b>OTHERS</b>                       |   |   |
| LED Video Light                     |   | —   |
| Accessory Shoe                      |   | —   |
| <b>STANDARD ACCESSORIES</b>         |   |   |
| AC Adaptor                          |   | Yes   |
| AC Cable                            |   | Yes   |
| DC Cable                            |   | Included AC Adaptor   |
| Rechargeable Battery Pack           |   | Min. 895 mAh/Lithium-Ion  |
| AV multi Cable                      |   | —   |
| AV Cable                            |   | Yes   |
| IR Remote                           |   | —   |
| Shoe adaptor                        |   | —   |
| USB Cable                           |   | Yes   |
| SD Memory Card                      |   | —   |
| Included Software                   |   | VideoCam Suite 3.0  |
| Lens hood                           |   | —   |
| Stylus Pen                          |   | —   |