

PE3WU3

APC Essential SurgeArrest 3 Outlet Wall Tap with
5V, 3.4A 2 Port USB Charger, 120V



Overview

Lead time	Usually in Stock
-----------	------------------

General

Provided equipment	User manual
--------------------	-------------

Physical

Colour	White
Depth	5.3 cm
Height	13.5 cm
Net weight	0.2 kg
Width	9.5 cm

Input

Input power	1800 W
Maximum line current	15 A
Network frequency	50/60 Hz
Plug standard	NEMA 5-15P
Maximum input current	15 A
Switching current capacity	15 A
Input voltage	120 V

Output

Number of power socket outlets	3
Outlet standard	NEMA 5-15R

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Conformance

Product certifications	CULus
Standards	UL 498 UL 1310 UL 1449
Equipment protection policy	Lifetime : \$50000

Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 %
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 %
Storage altitude	0.00...15240.00 m

Surge Protection and Filtering

Response time	1 ns common mode
Common mode rejection	40 dB
Peak current	24 kA common mode 12 kA normal mode
Surge energy rate	540 J

Packing Units

Package 1 Weight	0.29 kg
Package 1 Height	18.1 cm
Package 1 width	22 cm
Package 1 Length	5.5 cm
SCC14	10731304343667
Number of Units in Package 2	6
Package 2 Weight	1.98 kg
Package 2 Height	228.60 mm
Package 2 width	203.20 mm
Package 2 Length	279.40 mm
Number of Units in Package 3	480

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information

Contractual warranty

Warranty	Lifetime
----------	----------