

# GVSUPS30KB4GS

Galaxy VS UPS 30kW 480V, 2 internal 9Ah smart modular battery strings, expandable to 4, Start-up 5x8



## Overview

Description	Highly efficient, easy-to-deploy 30kW, 480V 3-phase UPS that brings best-in-class power protection and low total cost of ownership to edge, small and medium data centers, as well as to critical infrastructure in commercial and industrial applications. Includes 5x8 start-up service and 2 smart high-capacity modular battery strings, expandable to 4 strings for extended runtime. Runtime charts available in the Documents tab.
Model Name	Galaxy VS UPS 30kW 480V, 2 internal 9Ah smart modular battery strings, expandable to 4, Start-up 5x8
Includes	Battery modules ship installed , Dust filter , EcoStruxure Ready ((UPS)) , Installation guide , Integrated network management , Power modules ship installed , Start-Up Service
Standard Lead Time	Usually Ships within 2 Weeks
Product Distribution	Antigua And Barbuda , Aruba , Bahamas , Barbados , Belize , Bermuda , Brazil , Canada , Colombia , Costa Rica , Cuba , Dominican Republic , Ecuador , El Salvador , Guatemala , Haiti , Honduras , Jamaica , Mexico , Netherlands Antilles , Nicaragua , Panama , Puerto Rico , Trinidad And Tobago , Turks And Caicos Islands , United States , Venezuela , VIRGIN ISLANDS (UNITED STATES)

## General

Bypass Voltage Tolerance	+/-10%
--------------------------	--------

## Output

Output Power Capacity	30.0 KW / 30.0 kVA
Max Configurable Power (Watts)	30.0 KW / 30.0 kVA
Nominal Output Voltage	480 3PH
Output Frequency (sync to mains)	50 Hz , 60 Hz
Crest Factor	2.5
Crest Factor	Double Conversion Online
Waveform Type	Sine wave
Output Voltage Tolerance	+/-1% after 50ms
Overload Operation	150% for 1 minute 125% for 10 minutes
Bypass	Built-in Static Bypass

## Input

Nominal Input Voltage	480 3PH
Input Frequency	40 - 70 Hz
Input voltage range for main operations	408 - 552 (480) V
Maximum Input Current	45 A
Maximum Short Circuit Withstand (I <sub>sc</sub> )	65.0
Input Total Harmonic Distortion	Less than 3% for full load

## Batteries & Runtime

Battery Type	VRLA
Nominal Battery Voltage	480V
End of Discharge Battery Voltage	384 Vdc
Maximum Available Short Circuit Current	65 kA
End of Discharge Maximum Battery Current	81 A

## Communications & Management

Interface Port(s)	GVSAIO_BypassCabinetCables_UL , GVSAIO_MBP_UL , GVS_350mm_AirFilter , GVS_350mm_Seismic
Available SmartSlot™ Interface Quantity	1
Control panel	Touch Screen LCD User Interface
Audible Alarm	Audible and visible alarms prioritized by severity

## Physical

Maximum Height	1485.0 mm
Maximum Width	521.0 mm
Maximum Depth	847.0 mm
Net Weight	460.0 kg
Shipping Weight	490.0 kg
Shipping Height	1680.0 mm
Shipping Width	640.0 mm
Shipping Depth	990.0 mm
Color	Gloss level 85% , RAL 9003 , White

## Environmental

Operating Environment	0 - 40 °C
Operating Relative Humidity	0 - 95 (non-condensing) %
Operating Elevation	0-984.3 meters
Storage Temperature	-15 - 40 °C
Storage Relative Humidity	10 - 80 (non-condensing) %
Storage Elevation	0-3000 meters
Audible noise at 1 meter from surface of unit	61.000 dB
Online Thermal Dissipation	3175.000 BTU/hr
Protection Class	IP 20

## Conformance

Approvals	CSA C22.2 NO. 107.3 , FCC Part 15 Class A , IEC 60721-4-2 Level 2M2 , IEC 62040-3 , UL 1778 5th edition
Standard warranty	1 year on-site repair or replace with factory authorized Start-Up

## Sustainable Offer Status

RoHS	Compliant
REACH	REACH: Contains SVHCs