Product data sheet Characteristics

XB102XX1XS

SmartUPS Industrial Battery 100Ah 12VDC **Extended Temperature Shelf Mount**



O	V	e	rν	Ίe	W

Lead time	Usually in Stock	
2000 11110		<u></u>

General

Provided equipment	User manual	
		,

Physical

Overview		
Lead time	Usually in Stock	
General		
Provided equipment	User manual	
Physical		
Depth	33 cm	
Height	21.8 cm	
Product weight	31.03 kg	
Width	17.3 cm	
Conformance		
Product certifications	UL recognized	
Marking	CE Mark	
Environmental		
Ambient air temperature for operation	-2055 °C	
Ambient air temperature for storage	-2050 °C	
Batteries & Runtime		
Number of battery blocks per string	4	

Conformance

Product certifications	UL recognized
Marking	CE Mark

Environmental

Ambient air temperature for operation	-2055 °C	- \$
Ambient air temperature for storage	-2050 °C	<u>ه</u> .—

Batteries & Runtime

Number of battery blocks per string	4	a su
Number of battery free slots	0	ed as
Number of battery filled slots	0	hend
Device mounting	Stand alone battery stack	not ii
Battery voltage	12 V	- si uoi
Battery type	Gel cell	entat

Packing Units

Package 1 Weight	31 75 ka	C
	31.73 kg	
		•

EU RoHS Directive	Not applicable, out of EU RoHS legal scope	
Offer Sustainability		
Package 1 Length	35.6 cm	
Package 1 width	20.3 cm	
Package 1 Height	27.9 cm	

2 years repair or replace

Warranty