

# Product data sheet

Specifications



## APC Smart-UPS Ultra, 2200VA 120V 1U, with Lithium-Ion Battery, with Network Management Card Embedded

SRTL2K2RM1UNC

### Main

<b>Main Input Voltage</b>	120 V 125 V
<b>Other Input Voltage</b>	120 V 125 V
<b>Main Output Voltage</b>	120 V
<b>Other Output Voltage</b>	120 V 125 V
<b>Rated power in W</b>	2200 W
<b>Rated power in VA</b>	2200 VA
<b>Input Connection Type</b>	NEMA 5-20P
<b>Output connection type</b>	3 NEMA 5-20R 1 NEMA L5-20R
<b>Number of rack unit</b>	1U
<b>Cable length</b>	2.44 m
<b>Number of cables</b>	1
<b>Battery type</b>	Li-Ion (Lithium-Ion)
<b>Provided equipment</b>	RJ45 cable USB cable Country-specific detachable power cord Rack mounting brackets Rack mounting support rails Installation guide Warranty card

### General

<b>Redundant</b>	No
------------------	----

### Physical

<b>Colour</b>	Silver grey
<b>Height</b>	43 mm
<b>Width</b>	432 mm
<b>Depth</b>	560 mm
<b>Net weight</b>	15.9 kg
<b>Mounting preference</b>	No preference
<b>Mounting mode</b>	Rack-mounted with kit Tower-mounted with kit

Two post mountable	1
USB compatible	Yes

## Input

Network frequency	50/60 Hz
-------------------	----------

## Output

Maximum configurable power in W	2200 W
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Crest factor	3 : 1
UPS type	On-Line
Wave type	Sine wave
Bypass type	Internal bypass (automatic and manual)
Maximum configurable power in VA	2200 VA


## Conformance

Product certifications	UL/cUL listed FCC
Standards	UL 1778 CSA C22.2 No 107.3-05 FCC part 15 class A

## Environmental

Ambient air temperature for operation	0...40 °C
Relative humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient air temperature for storage	-15...45 °C
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0.00...15240.00 m
Acoustic level	55 dB
IP degree of protection	IP20

## Batteries & Runtime

Battery recharge time	1.5 h
Battery voltage	50 V
Battery charger power	448 W
Battery power in VAh	312 VAh runtime
Battery option	SRTL50RMBP1U-LI 1 1452 VAh SRTL50RMBP1U-LI 2 2592 VAh SRTL50RMBP1U-LI 3 3732 VAh SRTL50RMBP1U-LI 4 4872 VAh SRTL50RMBP1U-LI 5 6012 VAh
Extended runtime	1
Replacement battery	<a href="#">APCRBC173-LI</a> 

## Communications & Management

Control panel	Multifunction LCD status and control console
Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	278.2 mm
Package 1 Width	564 mm
Package 1 Length	764 mm
Package 1 Weight	24.18 kg

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	<a href="#">China RoHS declaration</a> Product out of China RoHS scope. Substance declaration for your information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins

## Contractual warranty

Warranty	5 years repair or replace
----------	---------------------------

## Recommended replacement(s)