

Product data sheet

Specifications



APC Smart-UPS Ultra Tower Isolation/Step-Down Transformer, 5kVA, 8x 5-20R & 2x L6-20R & 1x L6-30R & 1x L14-30R NEMA outlets

SRTL5KTf

Overview

| | |
|-----------|------------------|
| Lead time | Usually in Stock |
|-----------|------------------|

Main

| | |
|---------------------------|------------------------------------|
| Main Input Voltage | 208 V |
| Product or Component Type | Uninterruptible power supply (UPS) |
| Main Output Voltage | 120 V |
| Other Output Voltage | 240 V |
| Rated power in VA | 5 kVA |
| Input Connection Type | NEMA L6-30P |
| Cable length | 3 ft (0.9 m) |
| Number of cables | 1 |
| Provided Equipment | User Manual |

Physical

| | |
|---------------------|--------------------------|
| Color | Black |
| Height | 17.008 in (43.2 cm) |
| Width | 5.1 in (13 cm) |
| Depth | 26.0 in (66 cm) |
| Net Weight | 125.002 lb(US) (56.7 kg) |
| Mounting preference | No preference |
| Mounting Mode | Rack-mounted with kit |

Input

| | |
|-----------------|----------|
| Load Capacity | 5000 VA |
| Input Frequency | 50/60 Hz |

Output

| | |
|--------------------------------------|--------------|
| Maximum Total Current Draw per Phase | 5000 A |
| Number of power socket outlets | 12 |
| Number of power socket outlets | 8 NEMA 5-20R |

Conformance

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

| | |
|------------------------|---------|
| Product Certifications | CSA |
| Standards | UL 1778 |

Environmental

| | |
|---------------------------------------|--|
| Ambient Air Temperature for Operation | 32...104 °F (0...40 °C) |
| Relative Humidity | 0...95 % non-condensing |
| Operating altitude | 0...10000 ft |
| Ambient Air Temperature for Storage | 5...113 °F (-15...45 °C) |
| Storage Relative Humidity | 0...95 % non-condensing |
| Storage altitude | 0...50000 ft (0.0000000000...15240.0000000000 m) |

Ordering and shipping details

| | |
|-------------------|--------------|
| GTIN | 731304437048 |
| Country of origin | PH |

Packing Units

| | |
|------------------------------|------------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 13.7 in (34.7 cm) |
| Package 1 Width | 38.6 in (98 cm) |
| Package 1 Length | 23.7 in (60.3 cm) |
| Package 1 Weight | 140.0 lb(US) (63.5 kg) |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 5 years repair or replace |
|----------|---------------------------|

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.


[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)



Transparency

Well-being performance

 Mercury Free

| | |
|--------------------------|--|
| Reach Regulation | REACH Declaration |
| Eu Rohs Directive | Compliant with Exemptions |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information. |
| Environmental Disclosure | Product Environmental Profile |
| Weee | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |
| Circularity Profile | End of Life Information |