

Cisco Compatible 10Gbase-SR SFP+ Transceiver with DDM, MMF, 850nm, 300M, LC

MODEL NUMBER: **N286-10GSR-MDLC**



Description

Tripp Lite N286-10GSR-MDLC, SFP+ (mini-GBIC) transceiver module, is designed for use with Cisco networking equipment, and is functionally equivalent to Cisco part number SFP-10G-SR=. This transceiver is manufactured to meet or exceed the specifications of the original Cisco unit, and to comply with Multi Source Agreement (MSA) standards. Tripp Lite guarantees 100% compatibility with Cisco networking hardware, and will initialize and perform identically to an OEM transceiver. See "Features" tab for a list of most common Cisco devices used with this model transceiver.

Features

- Cisco switch compatible...Comparable to SFP-10G-SR=
- Compliant with SFP Multi-Source Agreement (MSA) standards
- 300 meter transmission distance using 10Gb 50/125 Multimode cabling
- 850nm wavelength VCSEL Laser
- Duplex LC Connector
- 10Gbase-SR transceiver supports data transfer rates up to 11.1Gbps using 10Gb 50/125 MMF cabling
- Electrical interface compliant with SFF-8431
- Supports Digital Diagnostic Monitoring (DDM)
- Hot-pluggable

Highlights

- Cisco switch compatible...Comparable to SFP-10G-SR=
- Compliant with SFP Multi-Source Agreement (MSA) standards
- 300 meter transmission distance using 10Gb 50/125 MMF cabling

System Requirements

- ASR 9000 Series Router
- ASR9000v Series Router
- ASR 901 Series
- Catalyst 2360 Series
- Catalyst 2960-S Series
- Catalyst 2960-X Series
- Catalyst 2960-XR Series
- Catalyst 3560-E Series
- Catalyst 3650 Series
- Catalyst 4500 Series
- Catalyst 4900 Series
- Nexus 2000 Series
- Nexus 3000 Series
- Nexus 4000 Series
- Nexus 5000 Series
- Nexus 7000 Series

Package Includes

- N286-10GSR-MDLC
- Quick Start Guide

Specifications

OVERVIEW	
Signal Range (m)	300
Fiber Type	50/125 - OM3



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

PHYSICAL	
Unit Dimensions (hwd / in.)	0.33 x 0.52 x 2.24
Unit Weight (lbs.)	0.05
ENVIRONMENTAL	
Storage Temperature Range	-40F to 185F
Relative Humidity	5 to 95% RH, Non-Condensing
Operating Temperature	32F - 158F
CONNECTIONS	
Connector A	LC (FEMALE)
WARRANTY	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.