Other Functions



Natural Light & with Flash

Natural Light & with Flash takes two photos in quick succession, one with flash and one without, eliminating the guesswork of flash photography.



Tracking Auto Focus

Great for capturing dynamic close-ups, this function keeps fast moving subjects in the frame and in focus, even when the zoom is fully extended.



Image Search

A convenient image search function lets you quickly and easily select photos based on any of several criteria.



YouTube™ / FACEBOOK Uploader In-camera software lets you mark your photos or videos for YouTube™ or FACEBOOK, for effortless uploading of data when the camera is connected to a PC running MyFinePix Studio.*

*Included with camera

Color Variations



SPECIFICATIONS

Number of effective pixels*1	14.4 million pixels
Image sensor	1/2.3-inch CMOS with primary color filter
Storage media	Internal memory (approx. 95MB), SD/SDHC/SDXC memory card*2
Lens focal length full-apertu constitution	F3.9 (Wide) - F4.9 (Telephoto)
Digital zoom	Approx. 6.8× (up to approx. 34×, with 5× optical zoom)
Aperture	F3.9 / F6.2 (Wide), F4.9 / F8 (Telephoto)
Focus distance (from lens surface)	Normal: (Wide) Approx. 60 cm to infinity / 2.0 ft. to infinity, (Telephoto) Approx. 1.0 m to infinity / 3.3 ft. to infinity Macro: (Wide) Approx. 9 cm - 80 cm / 3.5 in 2.6 ft., (Telephoto) Approx. 40 cm - 80 cm / 1.3 ft 2.6 ft.
Sensitivity	Auto, ISO 100/200/400/800/1600/3200 (Standard Output Sensitivity)
lmage stabilizer	CMOS shift type
LCD monitor	2.7-inch, Approx. 230,000 dots, TFT color LCD monitor, Approx. 96% coverage
Movie recording	1920×1080 pixels, 1280×720 pixels, 640×480 pixels (30 frames/sec.) with monaural sound Zoom function can be used.
Power supply	Li-ion battery NP-50A (included)
Dimensions	102.7 (W) × 71.3 (H) × 27.4 (D) mm / 4.0 (W) × 2.8 (H) × 1.0 (D) in. (excluding projections)
Weight	Approx. 195 g / 6.8 oz. (including battery and memory card)
Guide to the number of availa frames for battery operation	Approx. 300 frames (AUTO mode)
Accessories included	Li-jon hattery NP-50A Rattery charger RC-50A Plug adapter LISR cable. Hand stran. CD-ROM. Owner's manual

*1 : Number of effective pixels: The number of pixels on the image sensor which receive input light through the optical lens, and which are effectively reflected in the final output data of the still image *2.* Please see the Fuirfilm website to check memory card connactibility.

Microsoft, Windows and Windows logo are trademarks, or registered trademarks of Microsoft Corporation in the United States and/or other countries. Macintosh and Mac OS are trademarks of Apple Computer, Inc., registered in the U.S. and other countries. 50 logo is a trademark. All other trademarks

For more information, please visit our Website

Specifications and design are subject to change without notice.

All sample photos are simulated images.

http://www.fujifilm.com/products/digital_cameras/index.html

FUJIFILM FUJIFILM Corporation



FINEPIX X2100



14 Megapixels | Fujinon 5× Optical Zoom | 2.7-inch LCD





600cd Anti Reflection LCD





In Bright Light





nderwater

The bright, clear 2.7-inch LCD features an anti-reflective coating for excellent visibility, even in full sunlight. It also gives you a great view of the underwater world.

Shockproof Bumper

A shockproof bumper protects the LCD in the midst of the action.

FUJIFILM

Double Lock

The battery compartment is sealed with a double lock as an extra waterproofing safeguard when using the camera underwater or in the field.

for the Great Outdoors

A bright LED light shows you the way in the dark.



10m/32.8ft. Waterphoof 2m/6.6ft.

m/6.6ft. ockproof

-10°C/14°F Freezeproof

Anti-slip Rubber Grip

The shaped anti-slip rubber grip lets you keep a firm hold on the camera with bare or gloved hands.

Water-repellent Lens Coating

The reinforced lens cover is treated with a water-repellant coating – just shake the water off the lens and go right on shooting.



FUJIFILM Quality: Take It With You

Full HD Movies

& Micro HDMI

Capture photos and movies in high-definition 16:9 format for full-screen HDTV image display. A handy Micro HDMI connection lets you plug the camera directly into your TV or entertainment system.








14 Megapixels

Capture sharp, high-resolution photos and video, suitable for enlarged printing or display on a big screen.



New Long-life Li-ion Battery

Capable of shooting more than 300 frames on a single charge, the long-life Li-ion battery keeps up with your most active itingraries



CMOS-shift Image Stabilization

CMOS-shift image stabilization combines with high sensitivity to greatly reduce the effects of camera shake and subject blur for crisp, clear shots in a variety of demanding conditions.





Conventional digital camera

FinePix XP150