



VM-1110xl

1:10 Balanced Mono Audio Distribution
Amplifier



The VM-1110xl is a high-performance distribution amplifier for balanced mono audio signals on XLR connectors. It can also be configured as a 1:5 distribution amplifier for stereo balanced audio signals

FEATURES

Level (Gain) Controls

Dual Mode - Configure as 1:10 (mono) or 1:5 (stereo) DA

S/N Ratio - 89.3dB

Standard 19" Rack Mount Size - 1U



TECHNICAL SPECIFICATIONS

INPUTS:	2 balanced stereo audio, +4dBu/50k Ω on XLR (F) connectors
OUTPUTS:	10 balanced stereo audio, +4dBu/50 Ω on XLR (M) connectors
MAX. OUTPUT LEVEL:	23.8Vpp
BANDWIDTH (-3dB):	>100kHz
S/N RATIO:	89.3dB
CROSSTALK:	-78dB
CONTROLS:	Level (x2): -0.7dB to +5.1dB, mode selector switches
COUPLING:	AC (input); DC (output)
AUDIO THD + NOISE:	0.081%
AUDIO 2nd HARMONIC:	0.006%
POWER CONSUMPTION:	230V AC, (115V AC USA), 6VA
INCLUDED ACCESSORIES:	Power cord
Product Dimensions	19" x 7.20 x 1U (43.6cm x 18.30cm x 4.36cm) W, D, H
Product Weight	2.8kg (6.2lbs) approx
Shipping Dimensions	55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21") W, D, H
Shipping Weight	3.6kg (8.0lbs) approx

