



KAC-CAM-50M

Video Camera



Choose the KAC-CAM-50M for smaller to medium rooms requiring a wider view. Both cameras are key components of the Kramer/ AudioCodes meeting rooms solutions, a bespoke collection of audio and video devices designed to create a fully integrated meeting room solution.

Compatibility is key, and these models excel with leading unified communications platforms such as Microsoft Teams and Zoom Rooms. Their ease of installation, thanks to a simple USB connection, and user-friendly operation, make them a top choice for enhancing your virtual meeting experience. Elevate your meetings with these state-of-the-art cameras, designed for simplicity, efficiency, and superior quality

FEATURES

- Crystal-clear image resolution at 4K/30fps resolution
- Intelligent zoom and facial recognition
- Seamless integration with Microsoft Teams, Zoom, and various UC platforms
- User-friendly setup and usage
- Powerful 10x digital zoom to easily focus on distant participants and objects
- Sleek, lightweight design with convenient mounting options for quick and effortless setup



TECHNICAL SPECIFICATIONS

Camera	Image Sensor 1/2.5 inch high quality 4K CMOS sensor Effective Pixels 8.28MP, 16:9 Video Output USB3.0, Type B. Support for audio signal output Video Resolution Main stream: 3840×2160 @30fps, 1920×1080P @30fps/25fps, 1280×720P@ 30fps/25fps Sub stream: 1280×720P @30fps/25fps, 640×480P @30fps/25fps, 320×172P @30fps/25fps Angle of View KAC-CAM-50M 91° (D) / 81°(H) / 54°(V) RXVCam50M 102°(D) / 100°(H) / 64°(V) Aperture KAC-CAM-50M F1.8 Minimum Illumination 0.1Lux (F1.8, AGC ON) Digital Zoom 10x DNR 2D & 3D DNR
USB	Operating System Windows 7 (1080P/720P), Windows 8.1, Windows 10, macOS™ 10.10 and above, Linux (UVC) Video Compression YUY2, MJPG, H.264, H.265 USB Protocol UVC, UAC PTZ Control Supports ePTZ Hardware Request 2.4 GHz Intel Core 2 Duo processor or better, 2GB capacity or more, USB 2.0, input (USB3.0 for 4K)
Power	Input Voltage DC 5V Input Current 1A (Max) Power Consumption 5W (Max)
Environmental Conditions	Store Temperature -10°C~+60°C Store Humidity 20%~90% Working Temperature -10C°~+50°C Working Humidity 20%~80%
General	Dimensions 220mm x 93.75mm x 56.5mm Application Indoor Accessories User manual, USB3.0 cable, remote controller
Product Dimensions	18.00cm x 6.37cm x 4.63cm (7.09" x 2.51" x 1.82") W, D, H
Product Weight	0.4kg (0.9lbs) approx
Shipping Dimensions	13.00cm x 26.00cm x 9.50cm (5.12" x 10.24" x 3.74") W, D, H
Shipping Weight	0.6kg (1.3lbs) approx