

2009

SDR-S26 Standard Definition Camcorder



Optical
70x
Ultra Zoom



70x Optical Zoom and Advanced OIS

Brings distant subjects up close while maintaining image quality



Intelligent Auto Mode

Face detection, Scene selector, Optical image stabilizer, Intelligent contrast control



YouTube™ Uploader

Shoot video and upload onto YouTube™

- One-touch DVD copying with BN1
- SD card slot (still/movie)
- MPEG2 recording
- One-touch navigation
- 2.7" wide LCD (Intelligent LCD)
- Editing software
- 2.0 hi-speed USB
- Mac (iMovie compatible)
- Stereo zoom mic
- 0.8 sec quick start
- Available in black, blue, silver and red



Panasonic
ideas for life

2009 **SDR-S26** Standard Definition Camcorder Specifications

SDR-S26	
GENERAL	
Power Supply	DC3.6V / 5.0V
Power Consumption	3.0W
Weight (w/o Battery)	approx. 235g (0.50lb)
Dimension (W x H x D)	56 x 65 x 107 [mm] (2.21 x 2.56 x 4.21 [inch])
Media	SD/SDHC Memory Card
On-Screen Display Language	Please refer to "OSD" sheet
IMAGE SENSOR	
Image Sensor	1/8" CCD
Total Pixels	0.8 megapixels
Effective Pixels	
Motion Image	0.29 megapixels [4:3], 0.38 megapixels [16:9]
Still Image	0.29 megapixels [4:3], 0.38 megapixels [16:9]
LENS SECTION	
Lens Brand	Panasonic
F Value	F1.9(WIDE) / 5.7(TELE)
Optical Zoom	70x
Digital Zoom	Digital Zoom; 70x-100x, Super Digital Zoom; 70x-3500x
Focal Length	1.5 - 105mm
35mm Film Camera Equivalent	45.6-3194mm (4:3), 37.3-2610mm (16:9) [Motion Image] 45.4-3180mm (4:3), 37.0-2592mm (16:9) [Still Image]
Filter Diameter	37mm
CAMERA SECTION	
Standard Illumination	1400 lx
Minimum Illumination	6lx (1/30 Low Light Mode) 2 lx (MagicPix®)
Image Stabilizer	Advanced O.I.S. [Optical Image Stabilization]
Focus	Auto / Manual
White Balance	Auto / Indoor / Outdoor / White set
Shutter Speed	
Motion Image	1/30-1/8000
Still Image	1/30-1/500
Iris	Auto / Manual
Backlight Compensation	Yes
MONITOR	
EVF	—
Monitor (LCD)	2.7" Wide LCD (123,200 pixels)
STILL IMAGE SECTION	
Recording Format	JPEG
Recording Image Size	
Still Picture	0.30 megapixels (640 x 480) [4:3], 0.23 megapixels (640 x 360) [16:9]
Simultaneous Recording	—
Still Image	—
Flash	—
DPOF	Max. 999 images
PictBridge	Yes
RECORDING SECTION	
Signal System	525 / 60i
Recording Format	MPEG2 [Motion Image]
Recording / Playback Mode	XP (10Mbps / VBR), (704 x 480) SP (5Mbps / VBR), (704 x 480) LP (2.5Mbps / VBR), (704 x 480)
Audio Recording System	Dolby Digital (2ch), MPEG1 AudioLayer 2
Microphone	Stereo mic. / Zoom mic.
Speaker	Dynamic type
Media Remaining Indication	Yes
INTERFACES	
AV	Out
HDMI	—
Microphone (stereo mini)	—
Headphones	—
USB	2.0 Hi-Speed
Video Component	—
OTHERS	
LED Video Light	—
Accessory Shoe	—
STANDARD ACCESSORIES	
AC Adaptor	Yes
AC Cable	Yes
DC Cable	Yes
Rechargeable Battery Pack	min. 940 mAh / Lithium-Ion
Video Component Cable	—
AV Cable	Yes
IR Remote	—
USB Cable	Yes
SD Memory Card	—
Included Software	VideoCam Suite V2.0