2010 LUMIX® FP1 FP3 DIGITAL CAMERA





FP1

FP3

ULTRA THIN, STYLISH DESIGN

Super slim, stylish design for on-the-go use.

3.0" TOUCH LCD (FP3)

Control all of your camera functions on a large easy to read touch panel LCD screen.



INTELLIGENT AUTO WITH MEGA O.I.S.

Automatically adjusts to ensure great photos under any condition.



SONIC SPEED AF

Lightning fast focus for capturing the action as it is taking place.

- Face Detection
- Intelligent Scene Selector
- 14.1 Megapixels (FP3), 12.1 Megapixels (FP1)
- Approximately 40MB Built-In Memory
- HD Movie Recording







2010 LUMIX® FP1/FP3 Digital Camera Specifications

	Disconsions (M		DMC-FP1	DMC-FP3
ETRICS	Dimensions (W x H x D) Weight		98.6 x 58.9 x 18.6 mm / excl. protrusions: 16.4 mm, (3.88 x 2.32 x 0.73 in / excl. protrusions: 0.65 in) Approx. 141g with Battery and SD Memory Card (0.31 ib); Approx. 121g without Battery and SD Memory Card (0.27 ib)	98.6 x 58.9 x 18.6 mm / excl. protrusions: 16.4 mm (3.88 x 2.32 x 0.73 in / excl. protrusions: 0.65 in) Approx. 145g with Battery and SD Memory Card (0.32 lb); Approx. 125g without Battery and SD Memory Card (0.28 lb)
OPTICS	Pixels CCD Lens	Camera Effective Pixels Sensor Size / Total Pixels / Filter	12.1 Megapixels 1/2.33-inch / 12.7 Total Megapixels / Primary Color Filter	14.1 Megapixels 1/2.33-inch / 14.5 Total Megapixels / Primary Color Filter
		Aperture	F3.5-F5.9 / Multistage Iris Diaphragm (F3.5-5.6 [W]/F5.9-7.1 [T])	F3.5–F5.9 / Multistage Iris Diaphragm (F3.5–5.6 [W]/F5.9–7.1 [T])
		Optical Zoom Focal Length	4x f=6.3-25.2mm (35-140mm in 35mm equiv.)	4x f=6.3-25.2mm (35-140mm in 35mm equiv.)
		Extra Optical Zoom (EZ)	4.9x (4:3 / 8M), 6.3x (4:3 / 5M), 7.8x (under 3M)	4.7x (4:3 / 10M), 6.8x (4:3 / 5M), 8.4x (under 3M)
		Intelligent Zoom Lens	LUMIX DC VARIO; 11 elements in 10 groups; (4 Aspherical Lenses / 7 Aspherical Surfaces / 1 ED Lens)	LUMIX DC VARIO; 11 elements in 10 groups; (4 Aspherical Lenses / 7 Aspherical Surfaces / 1 ED Lens)
		2-Speed Zoom Optical Image Stabilizer	- MEGA O.I.S. (Off / Auto / Mode1 / Mode2)	MEGA O.I.S. (Off / Auto / Mode1 / Mode2)
		Conversion Lens Compatibility		
	Encue	Digital Zoom Focusing Area	4x; (Max. 16.0 x combined with Optical Zoom without Extra Optical Zoom); (Max.31.3x combined with Extra Optical Zoom) Normal: Wide 50 cm - infinity/Tele 50 cm - infinity; Macro / Intelligent AUTO : Wide 10 cm - infinity / Tele 50cm - infinity	4x; (Max. 16.0 x combined with Optical Zoom without Extra Optical Zoom); (Max. 33.8 x combined with Extra Optical Zoom) Normal: Wide 50 cm - infinity / Tele 50 cm - infinity; Macro / Intelligent AUTO: Wide 10 cm - infinity/Tele 50cm - infinity
	Focus	Focus Range Display	Yes	Yes
		AF Assist Lamp Focus	Yes Normal / Macro, Zoom Macro, Quick AF (Always On)	Yes Normal / Macro, Zoom Macro, Quick AF (Always On), Touch AF
		AF Metering	Face / 9 pt/ 1pt	Face / 9 pt/ 1pt / Touch Area on screen
	Shutter	Shutter Speed Shutter Interval	Still: approx. 8 - 1/1600 sec; Starry Sky Mode : 15, 30, 60 sec approx. 1.0 sec	Still: approx. 8 - 1/1600 sec; Starry Sky Mode : 15, 30, 60 sec approx. 1.2 sec
	Finder IA	Viewfinder		· .
	In .	Face Recognition Optical Image Stabilizer	Photo & Movie	Photo & Movie
		Intelligent ISO Control Face Detection	Photo Photo	Photo Photo
		Intelligent Scene Selector	Photo (Portrait, Scenery, Night Portrait, Night Scenery, Sunset, Macro)	Photo (Portrait, Scenery, Night Portrait, Night Scenery, Sunset, Macro)
		Intelligent Exposure AF Tracking	· ·	· ·
		Digital Red-Eye Correction (Red-Eye Removal)	Photo	Photo
		iA Direct Button Intelligent Resolution Technology	Yes	Yes -
	File	File Format	Still Image: JPEG(DCF/Exif2.21); Motion picture: QuickTime Motion JPEG	Still Image: JPEG(DCF/Exif2.21); Motion picture: QuickTime Motion JPEG
	Interface	AVCHD Lite REC Mode Switch	[Recording] / [Playback]	[Recording] / [Playback]
		One-Touch Movie Button		
	Recording Modes	Mode Dial/Mode Button Still Image Scene Mode	Intelligent AUTO, Normal Picture, SCN, My SCN, Motion Picture Portrait, Soft Skin, Transform, Self-Portrait, Scenery, Sports, Night Portrait, Night Scenery, Food, Party, Candle Light, Baby1, Baby2, Pet,	Intelligent AUTO, Normal Picture, SCN, My SCN, Motion Picture Portrait, Soft Skin, Transform, Self-Portrait, Scenery, Sports, Night Portrait, Night Scenery, Food, Party, Candle Light, Baby1, Baby2, Pet,
		Movie Scene Mode	Sunset, High sensitivity, Hi-Speed Burst, Flash Burst, Starry Sky, Fireworks, Beach, Snow, Aerial photo, Film Grain, Photo Frame	Sunset, High sensitivity, Hi-Speed Burst, Flash Burst, Starry Sky, Fireworks, Beach, Snow, Aerial photo, Film Grain, Photo Frame
		Continuous Shooting Mode	High-speed Burst Mode: approx. 5.5 frames/sec (image priority); (recorded in 3M for 4:3, 2.5M for 3:2, 2M for 16:9)	High-speed Burst Mode: approx. 4.6 frames/sec (image priority); (recorded in 3M for 4:3, 2.5M for 3:2, 2M for 16:9)*
		Unlimited Consecutive Shooting Flash Burst Continuous Shooting Mode	1.8 frames/sec Max. 5 images (Standard mode)	1.5 frames/sec Max. 5 images (Standard mode)
		Motion Picture Recording 4:3	VGA: 640 x 480 pixels, 30fps (Motion JPEG)	VGA: 640 x 480 pixels, 30fps (Motion JPEG)
		16:9	QVGA: 320 x 240 pixels, 30 fps (Motion JPEG) WVGA: 848 x 480 pixels, 30 fps (Motion JPEG)	QVGA: 320 x 240 pixels, 30 fps (Motion JPEG) WVGA: 848 x 480 pixels, 30 fps (Motion JPEG)
		HD Movie	1280x720 pixels, 30fps (Motion JPEG)	1280x720 pixels, 30fps (Motion JPEG)
	Continuous Recordable Time (Motion Pictures	AVCHD Lite with Picture Quality Set to [SH] MOTION JPEG with Picture Quality Set to [HD]	· ·	· ·
RECORDING	Actual Recordable Time (Motion Pictures)	AVCHD Lite with Picture Quality Set to [SH]	· ·	
	Exposure Parameters	MOTION JPEG with Picture Quality Set to [HD] Exposure	- Program AE	Program AE
		Exposure Compensation	1/3 EV step. +/-2 EV	1/3 EV step, +/-2 EV
		Backlight Compensation Auto (AE) Bracketing	Yes (only in Intelligent AUTO mode)	Yes (only in Intelligent AUTO mode) -
		Multi-Aspect	Intelligence McMalete	Late Warred S. E. Wards
		Light Metering ISO Sensitivity	Intelligent Multiple IJSO / 80 / 100 / 200 / 400 / 800 / 1600; High Sensitivity (ISO 1600-6400)	Intelligent Multiple LISO / 80 / 100 / 200 / 400 / 800 / 1600; High Sensitivity (ISO 1600-6400)
	Image Parameters	Max. Auto ISO Setting Aspect Ratio	- 4:3/3:2/16:9	4:3/3:2/16:9
	image Parameters	Still Picture Recording 4:3	4000x3000(12M) / 3264x2448(8M EZ) / 2560x1920(5M EZ) / 2048x1536(3M EZ) / 640X480(0.3M EZ)	4320x3240(14M) / 3648x2736(10M EZ) / 2560x1920(5M EZ) / 2048X1536(3M EZ) / 640X480(0.3M EZ)
		3:2 16:9	4000 x 2672 (10.5M) 4000 x 2248 (9M)	4320 x 2880 (12.5M) 4320 x 2432 (10.5M)
		Image Quality		· ·
		White Balance Quick Menu	Auto Caylight Cloudy/Shade Halogen White Set, Selectable at Portrat, Soft Skin, Transform, Self Portrat, Sports, Baby, Pet, High Sensibity, Highspeed Burst, Photo Frame) Yes	Auto Daylight Cloudy Shader Halogen White Set, (Selectable at Portrait, Sort Skin, Transform, Self-Portrait, Sports, Baby, Pet, High Sensibility, Highspeed Burst, Photo Frame) Yes
		Color Mode/Color Effect	Standard, Vivid, Natural, Black & White, Sepia, Cool, Warm	Standard, Vivid, Natural, Black & White, Sepia, Cool, Warm
	Others	Picture Adjustment Still Image with Audio Recording	· ·	· ·
		GPS	· ·	
		Flip Animation Real-Time Histogram	·	
		Composition Guideline Auto Review	Yes (1 pattern)	Yes (1 pattern) 1sec. 2sec. Hold
		Easy Zoom/Zoom Resume	1 sec, 2 sec, Hold No / No	1sec, 2sec, Hold No / No
		Optical Zoom in Motion Picture		No.
		Macro Zoom Orientation Detector	Yes Yes	Yes Yes
		Scene Mode Help Screen Self Timer	Yes 2søc / 10sec	Yes 2sec / 10sec
		Focus Icon Select	Yes	Yes
	Display	Playback Mode Thumbnails/Zoomed Playback	Normal Playback, Slideshow, Category Playback, Favorites Playback 12.30-thumbrails / Max 16x	Normal Playback, Slideshow, Category Playback, Favorites Playback 12,30-thumbnails / Max 16x
PLAYBACK		Calendar Display/Dual-Image Playback	Yes / No	Yes / No
		Set Favorites/Rotate Image Playback Still Images with Audio	Yes / Yes	Yes / Yes -
		Playback Motion Picture	Yes (Motion JPEG)	Yes (Motion JPEG)
		Slideshow Mode Show Histogram	All / Category / Favorites BGM Effect (Natural / Slow / Swing / Urban / OFF)	All / Category / Favorites / BGM Effect (Natural / Slow / Swing / Urban / OFF) -
		Show Highlights		
	Delete	Delete Image DPOF Print Setting/Set Protection	Single / Multi / All / All except Favorites Yes / Yes	Single / Multi / All / All except Favorites Yes / Yes
	Edit	Resize/Trim/Aspect Conv./Leveling	Yes / Yes / No / No	Yes / Yes / No / No
		Copy/Title Edit/Text Stamp Cut Animation	Yes / No / Yes (only Baby, Pet, Travel) -	Yes / No / Yes (only Baby, Pet, Travel) -
		Video Divide	Olada (ANA) (ANA) - 1 COOC	Plant (ALM / APP 1) 1000P
		PictBridge Support OSD Language	Single / Multi / All / Favorites / DPOF English/Spanish	Single / Multi / All / Favorites / DP0F English/Spanish
£		Movie REC Guide Wind-Cut in Motion Picture		
SETUP		Travel Date / World Time	Yes / Yes	Yes / Yes
	Monitor	LCD Monitor Touch Panel	2.7" TFT Screen LCD Display (230K dots); Field of View: approx. 100%; AUTO Power LCD mode, Power LCD mode, High Angle mode	3.0" TFT Touch Screen LCD Display (230K dats), AR Coat; Field of View: approx. 100%; AUTO Power LCD mode, Power LCD mode, High Angle mode. Yes
	Tough	Waterproof	·	103 *
		Dustproof Freezeproof		·
		Shockproof	·	
	Flash	Built-in Flash External Flash	Auto, Auto/Red-eye Reduction, Forced On, Slow Sync./Red-eye Reduction, Forced Off; 0.3 - 4.9m (Mide/ISO Auto), 0.5 - 2.9m (Tele/ISO Auto)	Auto, Auto/Red-eye Reduction, Forced On, Slow Sync./Red-eye Reduction, Forced Off; 0.3 - 4.9m (Wide/ISO Auto), 0.5 - 2.9m (Tele/ISO Auto)
82	Media	Recording Media	Built-in Memory, SD Memory Card, SDHC Memory Card, SDXC Memory Card	Built-in Memory, SD Memory Card, SDHC Memory Card, SDXC Memory Card
OTHERS	Audio	Built-in Memory Microphone/Speaker	Approx. 40MB Mono / Yes	Approx. 40MB Mono / Yes
	Interface	Interface	Mono / Yes AV Output (NTSC), USB2.0 Full-speed, DC Input	Mono / Yes AV Output (NTSC), USB2.0 Full-speed, DC Input
	Network	VIERA Link TM		
		HDMI Output Power	ID-Security Li-ion Battery Pack (3.7V, Minimum: 695mAh) (Included); AC Adaptor (Input: 110-240V AC) (Optional)	ID-Security Li-lon Battery Pack (3.7V, Minimum: 695mAh) (Included); AC Adaptor (Input: 110-240V AC) (Optional)
	Power	Power		
	Power Standard Package	Battery Life (approx.) Included Software	300 pictures (CIPA Standard)*1 PHOTOfunSTUDIO 5.0 Edition; QuickTime; Adobe Reader	300 pictures (CIPA Standard)** PH0T0funSTUDIO 5.0 Edition; QuickTime; Adobe Reader