

Travel A/V Adapter: 2-in-1 Mini DisplayPort to HDMI or VGA Converter

Product ID: MDP2HDVGA



This travel adapter lets you connect your mDP enabled Ultrabook™ or laptop computer to any VGA or HDMI® display. The 2-in-1 Mini DisplayPort adapter is the perfect accessory for any of your Microsoft® Surface™ Pro devices equipped with mDP.

Connect to any HDMI or VGA display

Why carry multiple adapters when you only need one? Instead of keeping two different adapters on-hand, the MDP2HDVGA mDP travel adapter offers both VGA and HDMI outputs, so you'll be able to connect from your laptop mDP output to any modern boardroom or classroom display -- an ideal plug-and-play solution for BYOD (Bring Your Own Device) applications at the office.

Plus, because the converter supports video resolutions up to 1920x1200 or 1080p you can convert a Mini DisplayPort video source to HDMI or VGA without sacrificing video quality.







Maximize portability

The travel A/V adapter maximizes portability with a small footprint and lightweight design. The convenient design ensures the adapter is as portable as your laptop, fitting easily into your laptop bag or carrying case and eliminates the need to carry more than one adapter. With this adapter you can walk into virtually any boardroom ready to present, making a great first impression, and saving you the embarrassment of having to rummage through your bag looking for the right connector.

The 2-in-1 converter is compatible with the Intel Thunderbolt port on your computer and installs easily with no software or drivers required.

The MDP2HDVGA is backed by a 3-year StarTech.com warranty and free lifetime technical support.





Data Sheet

Certifications, Reports and Compatibility









Applications

- Keep the adapter with you while traveling, to connect to virtually any display you come across
- Connect your BYOD laptop/Ultrabook to a provided HDMI, or VGA display at work
- Connect a VGA, or HDMI display to your Mini DisplayPort laptop, to use as a secondary monitor

Features

- 2-in-1 design lets you connect your mDP computer to any HDMI or VGA display using a single adapter
- Maximize portability with a compact, lightweight adapter you can easily carry in your laptop bag
- Supports video resolutions up to 1920x1200 or 1080p
- Compatible with Intel Thunderbolt
- Plug-and-play installation
- No power adapter required



Data Sheet

| | Warranty | 3 Years |
|---|---|--|
| Hardware | Active or Passive Adapter | Active |
| | | Passive |
| | Adapter Style | Adapters |
| | Audio | Yes |
| | AV Input | Mini-DisplayPort |
| | AV Output | HDMI |
| | | VGA |
| Performance | Audio Specifications | 5.1 Surround Sound (Video source and destination dependant) |
| | Maximum Analog Resolutions | 1920x1200/1080p |
| | Maximum Digital Resolutions | 1920x1200/1080p |
| | Wide Screen Supported | Yes |
| Connector(s) | Connector A | 1 - Mini-DisplayPort (20 pin) Male |
| | Connector B | 1 - HDMI (19 pin) Female |
| | | 1 - VGA (15 pin, High Density D-Sub) Female |
| | | The UDMI next is a necessive next |
| Special Notes / Requirements | Note | The HDMI port is a passive port. The VGA port is an active port. |
| _ | Humidity | |
| Requirements | | The VGA port is an active port. |
| Requirements | Humidity | The VGA port is an active port. 10~85% RH |
| Requirements | Humidity Operating Temperature | The VGA port is an active port. 10~85% RH 0°C to 60°C (32°F to 140°F) |
| Requirements Environmental Physical | Humidity Operating Temperature Storage Temperature | The VGA port is an active port. 10~85% RH 0°C to 60°C (32°F to 140°F) -10°C to 70°C (14°F to 158°F) |
| Requirements Environmental Physical | Humidity Operating Temperature Storage Temperature Cable Length | The VGA port is an active port. 10~85% RH 0°C to 60°C (32°F to 140°F) -10°C to 70°C (14°F to 158°F) 5.9 in [150 mm] |
| Requirements Environmental Physical | Humidity Operating Temperature Storage Temperature Cable Length Color | The VGA port is an active port. 10~85% RH 0°C to 60°C (32°F to 140°F) -10°C to 70°C (14°F to 158°F) 5.9 in [150 mm] Black |
| Requirements Environmental Physical | Humidity Operating Temperature Storage Temperature Cable Length Color Product Height | The VGA port is an active port. 10~85% RH 0°C to 60°C (32°F to 140°F) -10°C to 70°C (14°F to 158°F) 5.9 in [150 mm] Black 0.5 in [1.3 cm] |
| Requirements Environmental Physical | Humidity Operating Temperature Storage Temperature Cable Length Color Product Height Product Length | The VGA port is an active port. 10~85% RH 0°C to 60°C (32°F to 140°F) -10°C to 70°C (14°F to 158°F) 5.9 in [150 mm] Black 0.5 in [1.3 cm] 7.5 in [19 cm] |
| Requirements Environmental Physical | Humidity Operating Temperature Storage Temperature Cable Length Color Product Height Product Length Product Width | The VGA port is an active port. 10~85% RH 0°C to 60°C (32°F to 140°F) -10°C to 70°C (14°F to 158°F) 5.9 in [150 mm] Black 0.5 in [1.3 cm] 7.5 in [19 cm] 2.3 in [58 mm] |
| Requirements Environmental Physical Characteristics Packaging | Humidity Operating Temperature Storage Temperature Cable Length Color Product Height Product Length Product Width Weight of Product | The VGA port is an active port. 10~85% RH 0°C to 60°C (32°F to 140°F) -10°C to 70°C (14°F to 158°F) 5.9 in [150 mm] Black 0.5 in [1.3 cm] 7.5 in [19 cm] 2.3 in [58 mm] 0.8 oz [22 g] |
| Requirements Environmental Physical Characteristics Packaging | Humidity Operating Temperature Storage Temperature Cable Length Color Product Height Product Length Product Width Weight of Product Package Height | The VGA port is an active port. 10~85% RH 0°C to 60°C (32°F to 140°F) -10°C to 70°C (14°F to 158°F) 5.9 in [150 mm] Black 0.5 in [1.3 cm] 7.5 in [19 cm] 2.3 in [58 mm] 0.8 oz [22 g] 0.6 in [15 mm] |
| Requirements Environmental Physical Characteristics Packaging | Humidity Operating Temperature Storage Temperature Cable Length Color Product Height Product Length Product Width Weight of Product Package Height Package Length | The VGA port is an active port. 10~85% RH 0°C to 60°C (32°F to 140°F) -10°C to 70°C (14°F to 158°F) 5.9 in [150 mm] Black 0.5 in [1.3 cm] 7.5 in [19 cm] 2.3 in [58 mm] 0.8 oz [22 g] 0.6 in [15 mm] 8.7 in [22 cm] |



Data Sheet

What's in the Box

Included in Package

1 - Mini DisplayPort™ to HDMI® / VGA Adapter

1 - Instruction manual

Product appearance and specifications are subject to change without notice.