

Data Sheet

HDMI Audio Extractor - 1080p

Product ID: HD2A



This HDMI® audio extractor lets you separate stereo audio from your HDMI video signal and connect it to a 3.5mm audio device, such as your stereo sound system or desktop speakers. You can also extract the audio from the HDMI signal and integrate it into an optical TOSLINK® application, using the included digital SPDIF adapter.

Hassle-free integration

Your latest consumer A/V equipment probably only offers an HDMI output. This can make it difficult to integrate devices, such as your new Blu-ray[™] player or computer system, with your existing audio equipment or desktop speakers.

The HDMI audio extractor is USB powered using the included power cable, for easy integration with your computer systems. The adapter also features a small footprint that discreetly blends into your hardware setup, for a uniform look.

www.startech.com
1 800 265 1844



Versatile connection options

With a 3.5mm audio output and a TOSLINK adapter included, the HDMI audio extractor lets you output audio to virtually any non-HDMI equipment, whether it's digital or analog. This makes the audio extractor great for any application where you need to connect your HDMI source to speakers that don't have an HDMI input - such as desktop speakers, or a classroom or boardroom sound system.

Maximum compatibility

The audio extractor is HDCP enabled and HDMI 1.3b compliant, to ensure compatibility with your HDMI device. Plus, the HDMI output supports resolutions up to 1920x1080 (1080p) at 60Hz, to fit any HD application.

The HDMI audio extractor can also be used with an inexpensive <u>dual-RCA composite adapter</u> (sold separately) to integrate the audio from your HDMI source into 2-channel RCA audio applications.

The HD2A is backed by a 2-year StarTech.com warranty and free lifetime technical support.



Data Sheet

Certifications, Reports and Compatibility





Œ F©



Applications

- Connect the audio from your HDMI source device to the speakers in a • boardroom or classroom
- Use the audio extractor with an inexpensive adapter (sold separately) • to output dual-RCA composite audio
- Convert the HDMI audio to dual-RCA composite using additional • adapters (sold separately)

Features

- Easily integrates the audio from your HDMI source with equipment • that doesn't support HDMI
- Extracts analog and digital audio with an included 3.5mm to SPDIF • adapter
- Expand the capabilities of the audio extractor by converting to RCA audio, using an inexpensive 3.5mm to RCA adapter (sold separately)
- Discreet installation with small footprint
- Supports resolutions up to 1080p with HDMI pass-through
- HDCP compliant
- USB-powered

www.startech.com 1 800 265 1844

StarTechcom

Hard-to-find made easy*

Data Sheet

HardwareAuioYesAV InputHDMIAV Output3.5 mm AudioAV OutputExplore - EP9323EPerformanceAudio Specifications0.1 stereo audioMaximum Digital Resolutions1080p (1920 x 1080)Maximum Digital ResolutionsU to 1080p (1920 x 1080)Maximum Digital Resolutions1.4 HDMI (19 pin) Female InputConnector Supported1.4 HDMI (19 pin) Female InputConnector Supported1.4 HDMI (19 pin) Female OutputConnector Type(s)1.4 USB Mini-Back (3 Position) Female OutputPowerMower Source1.4 USB Mini-Back (3 Position) Female OutputPowerMower Source0.6 Co 70°C (32°F to 158°F)Poster Supported-00°C to 30°C (14°F to 176°F)Physical Type(s)0.6 Co 10°C (14°F to 176°F)Physical FerrityForduct HeightProduct Height2.1 (IS Smm]Product Length2.4 In (60 mm]Product Length1.4 ca (39 g)Product Width2.6 in [14.3 cm]Mingin (Product5.6 in [14.3 cm]ProfermationSin (21.5 cm]Mark Supported Supported5.6 in [14.3 cm]Physical FerrityAcade LengthAcade Length5.6 in [14.3 cm]Mark Supported Height5.6 in [14.3 cm]Mark Supported		Warranty	2 Years
AV Output 3.5 mm Audio Chipset ID Explore - EP9323E Performance Audio Specifications 2.1 stereo audio Maximum Digital Resolutions 1080p (1920 x 1080) Supported Resolutions Up to 1080p (1920 x 1080) Wide Screen Supported Yes Connector (s) Connector A 1 - HDM1 (19 pin) Female Input Connector Type(s) 1 - USB Mini-Jack (3 Position) Female Output Connector Type(s) 1 - USB Mini-B (5 pin) Female Output Connector Type(s) 1 - USB Mini-B (5 pin) Female Output Power Over Source USB-Powered Environmental Humidity S% to 55% non-condensing Physical Operating Temperature 0°C to 70°C (32°F to 158°F) Characteristics Product Height 2.2 in [55 mm] Product Height 2.2 in [55 mm] Product Uidth 2.2 in [55 mm] Meight of Product 2.2 in [55 mm] Product Width 2.2 in [55 mm] Product Width S.6 in [14.3 cm] Package Height 5.6 in [14.3 cm] Pickage Width 6.6 in [14.3 cm] Pipping (Package) Weight 4.8 az [135 g] Wath's in the Box Flouded in Package	Hardware	Audio	Yes
Chipse I D Explore - EP9323E Performance Audio Specifications 2.1 stereo audio Maximum Digital Resolutions 1080p (1920 x 1080) Supported Resolutions Up to 1080p (1920 x 1080) Wide Screen Supported Yes Connector (s) Connector A 1 - HDMI (19 pin) Female Input Connector Type(s) 1 - USB Mini-Bck (3 Position) Female Output I - HDMI (19 pin) Female Output 1 - HDMI (19 pin) Female Output Connector Type(s) 1 - USB Mini-B (5 pin) Female Output Power Operating Temperature OS% to 95% non-condensing Power Source OPC to 70°C (32°F to 158°F) Storage Temperature -0°C to 80°C (14°F to 176°F) Physical Product Height 2.1 in [60 mm] Product Length 2.2 in [55 mm] Product Uridth 2.2 in [55 mm] Weight of Product 1.4 acz [39 g] Product Width 5.6 in [14.3 cm] Package Length 5.6 in [14.3 cm] Package Width 6.6 in [14.3 cm] Pipping (Package) Weight 4.8 ac [135 g] Widt's in the Box Flouded in		AV Input	HDMI
Performance Audio Specifications 2.1 stereo audio Maximum Digital Resolutions 1080p (1920 x 1080) Supported Resolutions Up to 1080p (1920 x 1080) Wide Screen Supported Yes Connector(s) Connector A 1 + HDMI (19 pin) Female Input Connector Type(s) 1 - 3.5 mm Mini-Jack (3 Position) Female Output 1 - HDMI (19 pin) Female Output 1 + HDMI (19 pin) Female Output Connector Type(s) 1 - USB Mini-B (5 pin) Female Power Power Source US8-Powered Environmental Humidity 5% to 95% non-condensing Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 80°C (14°F to 176°F) Physical Product Height 2.4 in [60 mm] Characteristics Product Height 2.2 in [55 mm] Weight of Product 1.4 oz [39 g] 1.4 oz [39 g] Packaging Information Package Length 5.6 in [14.3 cm] Package Width 6.7 in [17 cm] 5.0 inpl(2000000000000000000000000000000000000		AV Output	3.5 mm Audio
Maximum Digital Resolutions 1080p (1920 x 1080) Supported Resolutions Up to 1080p (1920 x 1080) Wide Screen Supported Yes Connector(s) Connector A 1 + HDMI (19 pin) Female Input Connector B 1 + 3.5 mm Mini-Jack (3 Position) Female Output Connector Type(s) 1 + USB Mini-B (5 pin) Female Output Power Power Source USB-Powered Environmental Hunidity 5% to 95% non-condensing Operating Temperature 0°C to 70°C (32°F to 158°F) Storage Temperature -10°C to 80°C (14°F to 176°F) Physical Product Height 2.4 in [60 mm] Physical Characteristics Product Height 2.2 in [55 mm] Packaging Product Width 2.2 in [55 mm] Product Width 1.4 oz [39 g] Package Ungth 5.6 in [14.3 cm] Package Width 6.7 in [17 cm] Package Width 6.8 in [2.135 g] Widts in the Box Indeud in Package Mathy in Package 1.4 HDMI audio extractor 1.2.5 ft. [780 mm] USB power cable		Chipset ID	Explore - EP93Z3E
Supported ResolutionsUp to 1080p (1920 x 1080)Wide Screen SupportedYesConnector(s)Connector A1 - HDMI (19 pin) Female InputConnector B1 - 3.5 mm Mini-Jack (3 Position) Female Output1 - HDMI (19 pin) Female OutputPowerPower SourceUSB-PoweredPower IPower SourceUSB-PoweredEnvironmentalHumidity5% to 95% non-condensingOperating Temperature0°C to 70°C (32°F to 158°F)Storage Temperature-10°C to 80°C (14°F to 176°F)Physical CharacteristicsProduct Height2.4 in [60 mm]Product Length2.4 in [60 mm]Product Width2.2 in [55 mm]Weight of Product1.4 oz [39 g]Packaging InformationPackage Height5.6 in [14.3 cm]Package Width5.6 in [14.3 cm]Package Width6.7 in [17 cm]Shipping (Package) Weight4.8 oz [135 g]What's in the BoxIncluded in PackageIncluded in Package1 - HDMI audio extractor 1 - 2.5 rft. [780 mm] USB power cable	Performance	Audio Specifications	2.1 stereo audio
Wide Screen SupportedYesConnector(s)Connector A1 - HDMI (19 pin) Female Input Connector BConnector B1 - 3.5 mm Mini-Jack (3 Position) Female Output 1 - HDMI (19 pin) Female OutputConnector Type(s)1 - USB Mini-B (5 pin) FemalePowerPower SourceUSB-PoweredEnvironmentalHumidity5% to 95% non-condensing 0perating TemperatureOperating Temperature0°C to 70°C (32°F to 158°F) Storage TemperaturePhysical CharacteristicsProduct HeightProduct Length2.4 in [60 mm] 1.4 oz [39 g]Packaging InformationPackage HeightPackage Kidth5.6 in [14.3 cm] Package WidthPackage Width5.6 in [14.3 cm] 4.8 oz [135 g]What's in the BoxInclude in PackageInclude in Package1 - HDMI audio extractor 1 - 2.5 ft. [780 mm] USB power cable		Maximum Digital Resolutions	1080p (1920 x 1080)
Connector(s)Connector A1 - HDMI (19 pin) Female InputConnector B1 - 3.5 mm Mini-Jack (3 Position) Female Output 1 - HDMI (19 pin) Female Output 1 - HDMI (19 pin) Female OutputPowerPower SourceUSB-PoweredPower SourceUSB-PoweredEnvironmentalHumidity5% to 95% non-condensing 0°C to 70°C (32°F to 158°F) storage TemperaturePhysical CharacteristicsProduct Height0.8 in [2 cm]Product Length2.4 in [60 mm] 1.4 oz [39 g]Packaging InformationPackage Height1.3 in [32 mm]Package Width5.6 in [14.3 cm] Package Width5.6 in [14.3 cm]Package Width6.7 in [17 cm] Sipping (Package) Weight4.8 oz [135 g]What's in the BoxInclude in Package1 - HDMI audio extractor 1 - 2.5 ft. [780 mm] USB power cable		Supported Resolutions	Up to 1080p (1920 x 1080)
Connector B 1 - 3.5 mm Mini-Jack (3 Position) Female Output 1 - HDMI (19 pin) Female Output Connector Type(s) 1 - USB Mini-B (5 pin) Female Power Power Source USB-Powered Environmental Humidity S% to 95% non-condensing Operating Temperature 0°C to 70°C (32°F to 158°F) Operating Temperature -10°C to 80°C (14°F to 176°F) Physical Characteristics Product Height 0.8 in [2 cm] Product Length 2.2 in [55 mm] Product Width 2.2 in [55 mm] Veight of Product 1.4 oz [39 g] Packageing Proformation Package Height 5.6 in [14.3 cm] Package Uidth 6.7 in [17 cm] 6.7 in [17 cm] Mat's in the Box Include in Package 4.8 oz [135 g] What's in the Box Include in Package 1 - HDMI audio extractor In 200 cstractor 1 - 2.5 tr. [780 mm] USB power cable		Wide Screen Supported	Yes
L - HDMI (19 pin) Female OutputConnector Type(s)1 - USB Mini-B (5 pin) FemalePowerPower SourceUSB-PoweredEnvironmentalHumidity5% to 95% non-condensingOperating Temperature0°C to 70°C (32°F to 158°F)Storage Temperature-10°C to 80°C (14°F to 176°F)Physical CharacteristicsProduct Height0.8 in [2 cm]Product Length2.4 in [60 mm]Product Width2.2 in [55 mm]Weight of Product1.4 oz [39 g]Packaging InformationPackage Length5.6 in [14.3 cm]Package Width5.6 in [14.3 cm]Package Width4.8 oz [135 g]What's in the BoxIncluded in Package1 - HDMI audio extractor 1 - 2.5 ft. [780 mm] USB power cable	Connector(s)	Connector A	1 - HDMI (19 pin) Female Input
Connector Type(s)1 - USB Mini-B (5 pin) FemalePowerPower SourceUSB-PoweredEnvironmentalHumidity5% to 95% non-condensing 0°C to 70°C (32°F to 158°F) storage TemperaturePhysical CharacteristicsProduct Height0.8 in [2 cm]Product Length2.4 in [60 mm] roduct Width2.2 in [55 mm]Packaging InformationPackage Height1.4 oz [39 g]Packaging InformationPackage Length5.6 in [14.3 cm] exacteristicsWhat's in the BoxIncluded in Package1- HDMI audio extractor i - 2.5 ft. [780 mm] USB power cable		Connector B	1 - 3.5 mm Mini-Jack (3 Position) Female Output
PowerPower SourceUSB-PoweredEnvironmentalHumidity5% to 95% non-condensingOperating Temperature0°C to 70°C (32°F to 158°F)Storage Temperature-10°C to 80°C (14°F to 176°F)Physical CharacteristicsProduct Height0.8 in [2 cm]Product Length2.4 in [60 mm]Product Width2.2 in [55 mm]Weight of Product1.4 oz [39 g]Packaging InformationPackage Height5.6 in [14.3 cm]Package Length5.6 in [14.3 cm]Package Width4.8 oz [135 g]What's in the BoxIncluded in Package1 - HDMI audio extractor 1 - 2.5 ft. [780 mm] USB power cable			1 - HDMI (19 pin) Female Output
EnvironmentalHumidity5% to 95% non-condensingOperating Temperature0°C to 70°C (32°F to 158°F)Storage Temperature-10°C to 80°C (14°F to 176°F)Physical CharacteristicsProduct HeightProduct Length2.4 in [60 mm]Product Width2.2 in [55 mm]Weight of Product1.4 oz [39 g]Packaging InformationPackage LengthPackage Width5.6 in [14.3 cm]Package Width6.7 in [17 cm]Shipping (Package) Weight4.8 oz [135 g]What's in the BoxIncluded in PackageIncluded in Package1 - HDMI audio extractor 1 - 2.5 ft. [780 mm] USB power cable		Connector Type(s)	1 - USB Mini-B (5 pin) Female
Operating Temperature0°C to 70°C (32°F to 158°F) -10°C to 80°C (14°F to 176°F)Physical CharacteristicsProduct Height0.8 in [2 cm]Product Length2.4 in [60 mm] Product Width2.2 in [55 mm]Product Width2.2 in [55 mm]Weight of Product1.4 oz [39 g]Packaging InformationPackage Height5.6 in [14.3 cm] 6.7 in [17 cm]Package Width5.6 in [14.3 cm]What's in the BoxIncluded in Package1 - HDMI audio extractor 1 - 2.5 ft. [780 mm] USB power cable	Power	Power Source	USB-Powered
Storage Temperature-10°C to 80°C (14°F to 176°F)Physical CharacteristicsProduct Height0.8 in [2 cm]Product Length2.4 in [60 mm]Product Width2.2 in [55 mm]Weight of Product1.4 oz [39 g]Packaging InformationPackage HeightPackage Length5.6 in [14.3 cm]Package Width6.7 in [17 cm]Shipping (Package) Weight1.4 oz [135 g]What's in the BoxIncluded in Package	Environmental	Humidity	5% to 95% non-condensing
Physical CharacteristicsProduct Height0.8 in [2 cm]Product Length2.4 in [60 mm]Product Width2.2 in [55 mm]Weight of Product1.4 oz [39 g]Packaging InformationPackage HeightPackage Length5.6 in [14.3 cm]Package Width6.7 in [17 cm]Shipping (Package) Weight4.8 oz [135 g]What's in the BoxIncluded in PackageIncluded in Package1 - HDMI audio extractor 1 - 2.5 ft. [780 mm] USB power cable		Operating Temperature	0°C to 70°C (32°F to 158°F)
Characteristics Product Length 2.4 in [60 mm] Product Width 2.2 in [55 mm] Weight of Product 1.4 oz [39 g] Packaging Information Package Height Package Length 5.6 in [14.3 cm] Package Width 6.7 in [17 cm] Shipping (Package) Weight 4.8 oz [135 g] What's in the Box Included in Package Included in Package 1 - HDMI audio extractor 1 - 2.5 ft. [780 mm] USB power cable		Storage Temperature	-10°C to 80°C (14°F to 176°F)
Product Width2.2 in [55 mm]Weight of Product1.4 oz [39 g]Packaging InformationPackage Height1.3 in [32 mm]Package Length5.6 in [14.3 cm]Package Width6.7 in [17 cm]Package) Weight4.8 oz [135 g]What's in the BoxIncluded in PackageIncluded in Package1 - HDMI audio extractor 1 - 2.5 ft. [780 mm] USB power cable	-	Product Height	0.8 in [2 cm]
Weight of Product 1.4 oz [39 g] Packaging Information Package Height 1.3 in [32 mm] Package Length 5.6 in [14.3 cm] Package Width 6.7 in [17 cm] Shipping (Package) Weight 4.8 oz [135 g] What's in the Box Included in Package Included in Package 1 - HDMI audio extractor 1 - 2.5 ft. [780 mm] USB power cable		Product Length	2.4 in [60 mm]
Packaging InformationPackage Height1.3 in [32 mm]Package Length5.6 in [14.3 cm]Package Width6.7 in [17 cm]Shipping (Package) Weight4.8 oz [135 g]What's in the BoxIncluded in PackageIncluded in Package1 - HDMI audio extractor1 - 2.5 ft. [780 mm] USB power cable		Product Width	2.2 in [55 mm]
Information Package Length 5.6 in [14.3 cm] Package Width 6.7 in [17 cm] Shipping (Package) Weight 4.8 oz [135 g] What's in the Box Included in Package Included in Package 1 - HDMI audio extractor 1 - 2.5 ft. [780 mm] USB power cable		Weight of Product	1.4 oz [39 g]
Package Width 6.7 in [17 cm] Shipping (Package) Weight 4.8 oz [135 g] What's in the Box Included in Package Included in Package 1 - HDMI audio extractor 1 - 2.5 ft. [780 mm] USB power cable		Package Height	1.3 in [32 mm]
Shipping (Package) Weight 4.8 oz [135 g] What's in the Box Included in Package 1 - HDMI audio extractor 1 - 2.5 ft. [780 mm] USB power cable		Package Length	5.6 in [14.3 cm]
What's in the Box Included in Package 1 - HDMI audio extractor 1 - 2.5 ft. [780 mm] USB power cable		Package Width	6.7 in [17 cm]
1 - 2.5 ft. [780 mm] USB power cable		Shipping (Package) Weight	4.8 oz [135 g]
	What's in the Box	Included in Package	1 - HDMI audio extractor
1 - Toslink adapter			1 - 2.5 ft. [780 mm] USB power cable
			1 - Toslink adapter

Product appearance and specifications are subject to change without notice.

www.startech.com 1 800 265 1844