

## 3-Port HDBaseT Extender Kit with 3 Receivers - 1x3 HDMI over CAT5 Splitter - Up to 4K

Product ID: ST124HDBT



This 3-Port HDBaseT™ extender kit lets you extend an HDMI® source to three remote locations, using HDBaseT technology. The kit includes three remote receiver units, and the transmitter features a local HDMI output, which gives you the ability to keep a fourth HDMI display at your local video source.

### **A complete extender kit that includes transmitter and receivers**

This all-in-one extender kit saves you the complications and compatibility issues that can happen if you're not using the correct receivers. It's perfect for use in corporate environments such as small or large offices, or in retail, hospitality, and educational establishments.

## Astonishing 4K picture quality from an impressive distance

With the A/V industry adopting 4K as its new high-resolution standard, long-range video distribution can be difficult, especially considering the 4K distance limitations on standard HDMI cables. You'll be amazed at how this HDBase-T extender kit can deliver your video signal to three different locations while maintaining 4K Ultra HD picture quality. You get four times the resolution of high-definition 1080p, even at 115 feet (35 m) away from your video source.

The extender is also backward compatible with 1080p at 230 feet (70 m), so you can comfortably use it to make any video source look great.

## Professional installation

HDBaseT technology offers a single-cable installation, so you can integrate this solution seamlessly using your existing CAT5e or CAT6 infrastructure. Plus, each device included with the HDBaseT extender kit is mountable, so you can keep the equipment out of sight in an equipment rack, or on a wall. This helps to reduce clutter and ensure a professional installation that doesn't draw your viewers' attention away from the content on your display. It's perfect for customer-facing displays in bars or restaurants.

## What is HDBaseT?

HDBaseT is a standardized, zero-latency video technology that's revolutionizing HDMI distribution. HDBaseT uses an advanced method of modulation that enables you to distribute uncompressed HDMI audio and video, along with additional signals, over a single Ethernet cable.

Offering greater versatility than traditional HDMI extenders, and longer distances than HDMI cables alone, HDBaseT is the clear choice for every integrator and system designer. It can do so much, with just a single cable.

The ST124HDBT is backed by a 2-year StarTech.com warranty and free lifetime technical support.

### Certifications, Reports and Compatibility



### Applications

- Route digital signage throughout large environments, such as schools, hospitals, arenas or shopping centers
- Extend a single entertainment source to multiple locations in hospitality settings such as bars, hotels or restaurants

### Features

- Extends your HDMI video signal to three remote HDMI displays, each in different locations
- A complete extender kit that includes the transmitter and three remote receivers
- Maintains UHD 4K up to 115 feet away, and HD 1080p up to 230 ft. away, over non-proprietary CAT5e or CAT6 cabling
- Mountable, to install securely and out of the way
- Dolby® TrueHD, DTS-HD MA Audio

<b>Hardware</b>	Warranty	2 Years
	Audio	Yes
	Cabling	Cat 5e UTP or better
	Daisy-Chain	Yes
	Ports	4
	Rack-Mountable	Yes
<b>Performance</b>	Max Distance	70 m / 230 ft
	Maximum 1080p Distance	70 m (230 ft.)
	Maximum 4K Distance	35 m (115 ft.)
	Maximum Cable Length	2755.9 in [70000 mm]
	Maximum Digital Resolutions	4096 x 2160 (4K) @ 30 Hz - maximum distance 35 m (115 ft.) 1920x1080 (1080p) - maximum distance 70 m (230 ft.)
	Supported Resolutions	4k x 2K (Ultra HD) @ 30 Hz 2560x1600 @ 60 Hz 1920x1200 1920x1080 (1080p) 1280x720 (720p)
<b>Special Notes / Requirements</b>	<b>Note</b>	CAT6 STP Cables provide protection against electromagnetic interference and cross-talk, and are highly recommended for use with this product.
<b>Power</b>	Center Tip Polarity	Positive
	Input Current	1.5A
	Input Voltage	100 - 240 AC
	Output Current	2.7A
	Output Voltage	24 DC
	Plug Type	4-pin DIN
	Power Consumption (In Watts)	64.8
	Power Source	AC Adapter Included
<b>Environmental</b>	Humidity	0% - 80 % RH (non-condensing)
	Operating Temperature	0°C to 40°C (32°F to 104°F)
	Storage Temperature	-10°C to 60°C (14°F to 140°F)
<b>Physical Characteristics</b>	Product Height	1.2 in [3 cm]
	Product Length	7.9 in [20 cm]

	Product Width	5.7 in [14.5 cm]
	Weight of Product	2.2 lb [1 kg]
<b>Packaging Information</b>	Package Height	3.9 in [98 mm]
	Package Length	14.3 in [36.3 cm]
	Package Width	11.8 in [29.9 cm]
	Shipping (Package) Weight	5.8 lb [2.6 kg]
<b>What's in the Box</b>	Included in Package	1 - 3-port HDBaseT extender
		3 - HDBaseT receivers
		1 - universal power adapter (NA / EU / UK / AU)
		4 - IR blasters
		4 - IR receivers
		1 - quick start guide

Product appearance and specifications are subject to change without notice.