

BC Personal 120V 350VA 180W Standby UPS, Ultra-Compact Desktop, 6 Outlets

MODEL NUMBER: BC350



Highlights

- 350VA ultra-compact 120V standby UPS
- Maintains AC output during power failures
- 3 UPS battery supported outlets, 3 surge-only outlets
- NEMA 5-15P input plug and 6 NEMA 5-15R outlets

Package Includes

- BC350 UPS System
- Instruction manual

Description

Tripp Lite's BC350 standby UPS offers power protection for PCs, workstations and other sensitive electronics in an attractive space saving, ultra-compact housing. Prevents data loss and system downtime by providing battery-supported AC output during brownouts and blackout conditions. 6 widely spaced output receptacles accommodate large transformer plugs without blocking outlets. 3 outlets with full battery support and surge suppression protect computers, monitors and other vital system components from loss of power; 3 additional surge suppression-only outlets are ideal for printers and other accessories not requiring battery support. Audible alarm and front panel LEDs offer status information regarding line and battery power operation. 350VA/180W power handling ability supports entry-level PCs for up to 12 min. during power failures. \$100,000 Ultimate Lifetime Insurance (U.S., Canada, and Puerto Rico only).

Features

- BC350 standby UPS offers complete protection from blackouts, brownouts and surges
- 6 widely spaced outlets accommodate large transformer plugs without blocking outlets
- 3 battery-supported outlets protect computer, monitor and vital system peripherals; 3 additional surge suppression-only outlets protect printers and other system accessories not requiring battery support
- Space saving right-angle input plug
- Provides battery-derived AC output during blackouts and brownouts
- 350VA/180W power handling ability supports a variety of PCs, workstations and other sensitive electronics
- Supports entry-level PC systems up to 12 min. during blackout conditions
- Optional [PDU B15](#) bypass PDU enable hot-swappable UPS replacement with no disruption to connected equipment
- Space-saving, ultra-compact housing fits almost anywhere

Specifications

OUTPUT	
Output Volt Amp Capacity (VA)	350
Output Watt Capacity (Watts)	180



Nominal Output Voltage(s) Supported	110V; 115V; 120V
Nominal Voltage Details	115v nominal output in battery mode
Frequency Compatibility	60 Hz
Output Voltage Regulation (Battery Mode)	+/- 5%
Output Receptacles	(6) 5-15R
UPS Output Receptacles (Surge Suppression Only)	3 UPS outlets, 3 surge-only outlets
Hot-Swap PDU options	PDUB15 (2U / 8 5-15R outlets)
Output AC Waveform (AC Mode)	Sine wave
Output AC Waveform (Battery Mode)	PWM sine wave
INPUT	
Rated input current (Maximum Load)	12A
Nominal Input Voltage(s) Supported	120V AC
UPS Input Connection Type	5-15P; Right-Angled
UPS Input Cord Length (ft.)	6
UPS Input Cord Length (m)	1.8
Recommended Electrical Service	15A 120V
Input Phase	Single-Phase
BATTERY	
Half Load Runtime (min.)	10 min. (90w)
DC System Voltage (VDC)	12
Expandable Runtime	No
USER INTERFACE, ALERTS & CONTROLS	
Switches	Combination switch controls on/off power status and self-test operation
Audible Alarm	Audible alarm indicates power-failure and overload status
LED Indicators	2 LEDs indicate power status and overload/check battery status
SURGE / NOISE SUPPRESSION	
UPS AC Suppression Joule Rating	380
UPS AC Suppression Response Time	Instantaneous
EMI / RFI AC Noise Suppression	Yes



PHYSICAL	
Installation Form Factors Supported with Included Accessories	Tower; Ultra-compact desktop
Primary Form Factor	Desktop
UPS Power Module Dimensions (hwd, in.)	3 x 10.5 x 5
UPS Power Module Dimensions (hwd, cm)	7.6 x 26.7 x 12.7
UPS Power Module Weight (lbs.)	7.7
UPS Power Module Weight (kg)	3.49
UPS Shipping Dimensions (hwd / in.)	4.5 x 12.5 x 7.8
UPS Shipping Dimensions (hwd / cm)	11.4 x 31.8 x 19.7
Shipping Weight (lbs.)	10
Shipping Weight (kg)	4.5
UPS Housing Material	ABS
Primary UPS Height (mm)	76
Primary UPS Width (mm)	267
Primary UPS Depth (mm)	127
Shipping Height (mm)	114
Shipping Width (mm)	318
Shipping Depth (mm)	198
ENVIRONMENTAL	
Operating Temperature Range	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
Storage Temperature Range	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
Relative Humidity	0 to 95%, non-condensing
AC Mode BTU / Hr. (Full Load)	46
Battery Mode BTU / Hr. (Full Load)	216
AC Mode Efficiency Rating (100% Load)	94%
COMMUNICATIONS	
Communications Interface	None
LINE / BATTERY TRANSFER	
Transfer Time	2-4 milliseconds



Low Voltage Transfer to Battery Power (Setpoint)	99
High Voltage Transfer to Battery Power (Setpoint)	139
SPECIAL FEATURES	
Cold Start (Startup in Battery Mode During a Power Failure)	Cold-start operation supported
Green Energy-Saving Features	Greater than 95% efficiency - GREEN UPS
CERTIFICATIONS	
UPS Certifications	Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico); Meets FCC Part 15 Category B (EMI)
WARRANTY	
Product Warranty Period (U.S. & Canada)	3-year limited warranty
Product Warranty Period (Latin America)	3-year limited warranty
Product Warranty Period (International)	2-year limited warranty
Product Warranty Period (Mexico)	3-year limited warranty
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$100,000 Ultimate Lifetime Insurance

© 2017 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>