

Waber-by-Tripp Lite 3-outlet Power Strip with 6-ft. Cord

MODEL NUMBER: 3SP



Description

The Waber-by-Tripp Lite 3SP power strip offers a convenient method of power distribution in workbench, wallmount or floor mount applications. Includes 3 NEMA 5-15R output receptacles with 1.75-inch center-to-center spacing, 6-foot AC line cord and keyhole mounting tabs for installation in a wide variety of applications. Corded, multi-outlet strip reduces cable clutter and permits connection of multiple electrical devices to a single AC wall socket. Unfiltered electrical pass-through makes the 3SP ideal for distributing alternate waveform UPS or generator power. Features a rugged all-metal housing, lighted power switch with transparent guard to prevent accidental shutoff, 15-amp resettable circuit breaker and attractive blue/gray color scheme.

PLUG/OUTLETS - Input: NEMA 5-15P/Output: 3 NEMA 5-15R

ELECTRICAL - 120VAC, 50/60Hz, 15A (Requires standard NEMA 5-15R wall receptacle)

FORMAT - Corded power distribution strip

Features

- Multi-outlet power strip offers convenient power distribution in workbench, wallmount or floor mount applications
- Includes 3 NEMA 5-15R output receptacles with 1.75-inch center-to-center outlet spacing
- Lighted power switch with transparent snap-over guard to prevent accidental shutoff
- Keyhole mounting tabs for installation on a wide variety of applications
- UL1363 (USA), cUL (Canada)
- 15-amp power handling capacity with circuit breaker
- 6-foot AC line cord

Specifications

OVERVIEW

Highlights

- 3 outlets
- 6-ft. cord
- 8.6 in. overall length
- Lighted master power switch

Applications

- Offers multiple outlet power distribution in workbench, wallmount or floor mount applications. Unfiltered electrical pass-through makes 3SP ideal for distributing alternate waveform UPS or generator power to protected equipment.

Package Includes

- 3SP Power Strip
- Warranty information
- Instruction manual



| | |
|---|---|
| Intended Application | Home/Office; Industrial/Factory Floor |
| OUTPUT | |
| Frequency compatibility | 50 / 60 Hz |
| Circuit Breaker (amps) | 15 |
| Outlet quantity / type | 3 NEMA 5-15R |
| Outlet spacing | 1.75 in. |
| Outlet orientation | Single row of 3 |
| INPUT | |
| Nominal Input Voltage(s) Supported | 120V AC |
| Recommended Electrical Service | 15A 120V |
| Input connection type | NEMA 5-15P |
| Input cord length (ft.) | 6 |
| Input cord length (m) | 1.8288 |
| Voltage compatibility (VAC) | 120 |
| LEDS ALARMS & SWITCHES | |
| Switches | Illuminated 2 position switch controls power to all outlets |
| Locking switch cover | Transparent locking switch cover prevents accidental shutoff |
| PHYSICAL | |
| Unit Dimensions (HWD/in) | 7.38 x 2.5 x 1.5 |
| Unit Dimensions (HWD/cm) | 18.7 x 6.35 x 3.8 |
| Material of construction | Metal |
| Integrated keyhole mounting tabs | Keyhole mounting tabs enable mounting to a variety of surfaces |
| Receptacle Color | Black |
| AC line cord color | Black |
| Style | Strip |
| Keyhole slot center to center measurement | Distance between keyhole tabs = 127mm; Distance between end tabs = 207.45mm |
| CERTIFICATIONS | |
| UL1363 (Power Tap) | UL1363 |
| cUL / CSA (Canada) | cUL |
| WARRANTY | |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| | |
|-------------------------------------|---------------------------|
| Product Warranty Period (Worldwide) | Lifetime limited warranty |
|-------------------------------------|---------------------------|

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.