



**Tripp Lite**  
1111 West 35th Street  
Chicago, IL 60609 USA  
Telephone: +(773) 869 1234  
E-mail: [saleshelp@tripplite.com](mailto:saleshelp@tripplite.com)

## Model #: SU6000RT4UHVG

### SmartOnline 6kVA On-Line Double-Conversion UPS, 4U Rack/Tower, 200-240V C19 outlets

#### Highlights



- 6kVA / 6000VA / 5400W on-line double-conversion UPS; 0.9 power factor
- 200/208/220/230/240V 50/60Hz output; High efficiency economy mode option
- 4U Rack/Tower compatible; Hot-swap power and battery modules
- USB, RS232 & EPO ports; SNMP/WEB and contact-closure card options
- Front panel LEDs with detailed LCD monitoring and control screen
- Expandable runtime with optional external battery packs
- Hardwire input (3 wire); C19 outlets

#### Description

Tripp Lite SU6000RT4UHVG 6000VA / 6kVA / 5400 watt on-line, double-conversion UPS system offers complete power protection for critical server, network and telecommunications equipment in a single 4U rack/tower compatible housing. Full-time active power conditioning provides clean, continuous dual-conversion AC output free of voltage fluctuations, power interruptions and line noise. Fault-tolerant auto-bypass prevents unexpected service interruptions during UPS overload or internal fault conditions. Detachable back panel PDU with manual bypass switch supports hot-swappable whole UPS replacement with no interruption to connected equipment. Single all-in-one rack / tower housing installs in only 4 rack spaces (4U) with a maximum installed depth of only 20.7 in. / 52.6cm. Maintains full-time sine wave output within 2% of selectable 200/208/220/230/240V nominal during brownouts as low 100V and overvoltages as high as 300V. Expandable runtime is supported with optional BP192V12-3U external battery packs. Battery independent restart ensures automatic UPS power-up without user interaction after lengthy power outages, even when batteries are expired and require replacement. Double-conversion operation converts raw input from AC to DC, then re-synthesizes output power back to perfect sine wave AC with enhanced protection from harmonic distortion, fast electrical impulses and other hard-to-solve power problems not addressed by other UPS types. Highly efficient operation in optional economy mode significantly reduces BTU heat output and operating energy costs. Network-grade AC surge and noise suppression. Supports detailed monitoring of equipment load levels, self-test data and utility power conditions via built-in RS-232 and USB interfaces. Optional SNMP/Web and contact-closure communications card accessories available. HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X. Included PowerAlert monitoring software offers detailed site power and UPS updates with support for safe auto-shutdown of connected systems as UPS batteries become depleted. Included software packages include PowerAlert Local, PowerAlert Network Shutdown Agent and PowerAlert Network Management System for complete support for a wide variety of application types. Supports Emergency Power Off (EPO) via built-in interface. Front panel LEDs and LCD readout with scroll controls support front-panel visual monitoring of all major UPS for a variety of control options to support advanced UPS settings and configurations. LED / LCD display panel rotates for viewing in rackmount or tower configurations. Hardwire input and 4 C19 outlets. Support for optional North American and International cordsets. External battery packs are field replaceable and hot swappable.

#### Features

- Tripp Lite SU6000RT4UHVG 6000VA / 6kVA / 5400 watt on-line, double-conversion UPS system in a single 4U rack/tower compatible housing (output is limited to 4992 watts when used at 208V with L6-30P input plug)
- Full-time active power conditioning maintains clean, continuous dual-conversion AC output free of voltage fluctuations, power interruptions and line noise
- Fault tolerant electronic bypass maintains utility output during a variety of UPS fault conditions
- Detachable back panel PDU contains hardwire input line cord connection, output receptacles and manual bypass switch to support hot-swappable whole UPS replacement with no interruption to connected equipment
- Hardwire input and 4 C19 output receptacles
- Included rail kit supports 4U 19 inch rackmount installation in 4 post racks
- Optional 2POSTRMKITHD supports installation in 2 post 19 inch racks (1 required for SU6000RT4UHVG)
- Optional 2-9USTAND supports upright tower placement (1 required for SU6000RT4UHVG)
- Maximum installed rack depth of only 20.7 in. / 52.6cm
- Maintains full-time sine wave output within 2% of selected 200/208/220/230/240V nominal in double conversion mode
- Corrects brownouts to 156V at full load (100V at 50% load or less)
- Corrects overvoltages to 290V at full load (300V at 90% load or less)

- Supports 50/60Hz operation for worldwide frequency compatibility
- Double-conversion operation offers full-time AC to DC, then DC to AC conversion to maintain perfectly regulated sine wave AC output with enhanced protection from harmonic distortion, fast electrical impulses and other hard-to-solve power problems not addressed by other UPS types
- High efficiency ECONOMY MODE operation significantly reduces BTU heat output and operating energy costs
- Network-grade AC surge and noise suppression
- Supports detailed monitoring of equipment load levels, self-test data and utility power conditions via built-in RS-232, USB and optional SNMP card slot interfaces
- UPS card slot supports one card-based network interface option (part # SNMPWEBCARD) or dry-contact monitoring accessory (part # RELAYIOCARD)
- Optional SNMPWEBCARD offers communications and control via secure remote web and network interfaces
- Optional RELAYIOCARD supports six configurable hard contact closure outputs for custom event notification
- Optional RELAYIOMINI interface module offers three configurable hard contact closure outputs for custom event notification (requires removal of USB interface module)
- HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X
- Includes Free PowerAlert monitoring software packages; PowerAlert LOCAL for desktops and small business networks, PowerAlert NSA (Network Shutdown Agent) for larger networks and PowerAlert NMS (Network Management System) for monitoring up to 250 SNMP-enabled UPS, PDU and other networking devices
- Front panel LEDs and LCD readout with scroll controls support front-panel visual monitoring of all major UPS functions with support for a variety of control options to support advanced UPS settings and configurations
- LED/LCD display panel rotates for viewing in rackmount or tower configurations
- Supports Emergency Power Off (EPO) via built-in interface
- Battery independent restart ensures automatic UPS power-up without user interaction after lengthy power outages, even when batteries are expired and require replacement
- BP192V12-3U external battery packs are field replaceable and hot swappable
- Some external battery configurations require the use of Tripp Lite's [External Battery Configuration Software](#) (see manual)
- Frequency conversion mode enables conversion of 60Hz to 50Hz or 50Hz to 60Hz (no de-rating)

## Specifications

OUTPUT	
Output Volt Amp Capacity (VA)	6000
Output kVA capacity (kVA)	6.0
Output Watt Capacity (watts)	5400
Output kW capacity	5.4
Output power factor	0.9
Output Capacity Details	Output capacity de-rates to 4992 watts when used at 208V with optional L6-30P line cord
Crest Factor	3:1
Nominal Output Voltage(s) Supported	200V; 208V; 220V; 230V; 240V
Frequency compatibility	50/60 Hz (auto-selectable)
Frequency compatibility details	Output frequency matches input nominal on startup; Frequency conversion mode enable conversion of 60Hz to 50Hz or 50Hz to 60Hz (no de-rating)
Output voltage regulation (line mode)	+/- 2%
Output voltage regulation (Economy line mode)	+/- 10%

<b>Output voltage regulation (Battery mode)</b>	+/- 2%
<b>Built-in UPS output receptacles</b>	4 C19 outlet(s)
<b>Output receptacle details</b>	Output receptacle and input connections are mounted on a detachable PDU backplate with bypass switch to enable hot-swappable power module replacement
<b>Output circuit breaker</b>	Two 20A breakers protect 2 C19 outlets each
<b>Output AC waveform (AC mode)</b>	Pure Sine wave
<b>Output AC waveform (battery mode)</b>	Pure Sine wave
<b>INPUT</b>	
<b>Rated input current (at maximum load)</b>	31.9A (200V), 30.6A (208V), 29A (220V), 27.7A (230V), 26.6A (240V)
<b>Nominal Input Voltage(s) Supported</b>	200V AC; 208V AC; 220V AC; 230V AC; 240V AC
<b>Nominal input voltage description</b>	Factory configured to 208V
<b>UPS input connection type</b>	Hardwire
<b>UPS input connection description</b>	Optional SU30ACORD offers L6-30P input cable
<b>UPS Input cord length (ft.)</b>	10
<b>UPS Input cord length (m)</b>	3
<b>Recommended Electrical Service</b>	40A (200/208v); 30A (220/230/240v)
<b>BATTERY</b>	
<b>Full load runtime (minutes)</b>	2 minutes (5400 watts)
<b>Half load runtime (minutes)</b>	8.5 minutes (2700 watts)
<b>Expandable battery runtime</b>	Runtime is expandable with external battery packs
<b>External battery pack compatibility</b>	<a href="#">BP192V12-3U</a> ; <a href="#">BP192V557C-1PH</a> ; <a href="#">BP192V787C-1PH</a> ; <a href="#">BP192V1037C-1PH</a> ; <a href="#">BP192V1407C-1PH</a>
<b>DC system voltage (VDC)</b>	192
<b>Battery recharge rate (included batteries)</b>	6 hours from 10% to 90% (internal batteries)
<b>Replacement battery cartridge (internal UPS battery replacement)</b>	<a href="#">RBC5-192</a>
<b>Battery Access</b>	Front panel battery access door

<b>Battery replacement description</b>	Hot-swappable, user replaceable internal batteries
<b>VOLTAGE REGULATION</b>	
<b>Voltage regulation description</b>	Online, double-conversion power conditioning
<b>Overvoltage correction</b>	Corrects overvoltages as high as 300V (
<b>Undervoltage correction</b>	Corrects undervoltages as low as 100 (
<b>LEDS ALARMS &amp; SWITCHES</b>	
<b>LED Indicators</b>	6 LEDs indicate line power, online mode, economy/bypass mode, on-battery, charger and AC output status; LCD screen offers additional information and control options
<b>Alarms</b>	Unique audible alarms for all major UPS, environmental and power conditions (see manual)
<b>Alarm cancel operation</b>	Alarm cancel switch
<b>Switches</b>	Includes main power off/on switch, plus 2 switches to set and execute scrollable LCD functions. A manual bypass switch featured on the detachable PDU allows for complete removal of the UPS during routine maintenance without disrupting power to connected loads.
<b>SURGE / NOISE SUPPRESSION</b>	
<b>UPS AC suppression response time</b>	Instantaneous
<b>EMI / RFI AC noise suppression</b>	Yes
<b>PHYSICAL</b>	
<b>Installation form factors supported with optional accessories</b>	2 post rackmount (2POSTRMKITWM); Tower (2-9USTAND)
<b>Primary form factor</b>	Rackmount
<b>UPS / Power Module dimensions in primary form factor (height x width x depth / inches)</b>	6.85 x 17.5 x 20.7
<b>UPS / Power Module dimensions in primary form factor (height x width x depth / cm)</b>	17.4 x 44.5 x 52.6
<b>Installed whole system total rack space height (rack spaces)</b>	4U
<b>Secondary form factor</b>	Tower
<b>UPS / Power Module weight (lbs)</b>	108
<b>UPS / Power Module weight (kg)</b>	49
<b>UPS Shipping dimensions (height x width x depth / inches)</b>	12.7 x 23.6 x 29.1

<b>UPS Shipping dimensions (height x width x depth / cm)</b>	32.3 x 59.9 x 73.9
<b>Shipping weight (lbs)</b>	156.5
<b>Shipping weight (kg)</b>	71.1
<b>UPS housing material</b>	Steel
<b>Cooling method</b>	Fans
<b>ENVIRONMENTAL</b>	
<b>Operating Temperature Range</b>	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
<b>Storage Temperature Range</b>	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
<b>Relative Humidity</b>	0 to 95%, non-condensing
<b>AC mode BTU / hr. (full load)</b>	1767
<b>AC economy mode BTU / hr. (full load)</b>	707
<b>Battery mode BTU / hr. (full load)</b>	1784
<b>AC economy mode efficiency rating (100% load)</b>	96%
<b>Operating Elevation (ft)</b>	0-3000m (0 to 10,000 ft.)
<b>Audible Noise</b>	60 dBA at front side 1 meter
<b>Operating Elevation (m)</b>	0-3000 m
<b>COMMUNICATIONS</b>	
<b>Communications interface</b>	USB (HID enabled); DB9 Serial; EPO (emergency power off); Slot for SNMP/Web interface
<b>Network monitoring port description</b>	Additional contact closure support with optional RELAYIOCARD and RELAYIOMINI interface cards. RELAYIOMINI installation requires removal of panel containing USB ports
<b>PowerAlert software</b>	Included
<b>Communications cable</b>	USB, DB9 serial and EPO cables included
<b>WatchDog compatibility</b>	Yes
<b>LINE / BATTERY TRANSFER</b>	
<b>Transfer time</b>	No transfer time (0 ms.) in online, double-conversion mode
<b>Transfer time (economy mode)</b>	8 ms. typical power failure response in optional economy mode
<b>Low voltage transfer to battery power (setpoint)</b>	156V (full load) / 100V (50% load or less, derates linearly)

<b>High voltage transfer to battery power (setpoint)</b>	280V (full load) / 300V (90% load or less)
<b>SPECIAL FEATURES</b>	
<b>Cold Start (startup in battery mode during a power failure)</b>	Cold-start operation supported
<b>High availability UPS features</b>	Automatic inverter bypass; Manual bypass switch; Detachable hot-swap PDU; Hot swappable UPS power module; Hot swappable batteries
<b>Green &amp; high efficiency features</b>	High efficiency economy mode operation; Schedulable daily hours of economy mode operation
<b>CERTIFICATIONS</b>	
<b>UPS Certifications</b>	Tested to UL1778 (USA); Tested to CSA (Canada); Meets FCC Part 15 Category A (EMI); ROHS (Restriction of Hazardous Substances)
<b>UPS Certification details</b>	IEC 61000-4-5 1995 B Surge Immunity
<b>WARRANTY</b>	
<b>Product Warranty Period (Worldwide)</b>	2-year limited warranty

## Related Items

### Optional Products

Related Model	Description	Qty.
<a href="#">BP192V12-3U</a>	BP192V12-3U - External Battery Pack for UPS System	1
<a href="#">RELAYIOMINI</a>	3 Relay I/O Mini-module	1
<a href="#">2POSTRMKITHD</a>	Enables 2-Post Rackmount Installation of 3U and Larger UPS, Transformer and Battery Pack Components	1
<a href="#">2-9U STAND</a>	Enables Tower Placement of Rackmount UPS Systems	1
<a href="#">SNMPWEBCARD</a>	For remote monitoring and control via SNMP, Web, or Telnet.	1
<a href="#">ENVIROSENSE</a>	Monitors temperature, humidity and contact-closure inputs. (Requires SNMPWEBCARD or switched PDU.)	1
<a href="#">RELAYIOCARD</a>	Programmable Relay I/O Card	1
<a href="#">WEXT3-SU6000HV</a>	3-Year Extended Warranty - For SU6000RT3UHV only	1
<a href="#">WEXT5-SU6000HV</a>	5-Year Extended Warranty - For SU6000RT3UHV only	1

More information, including related products, owner's manuals, and additional technical specifications, can be found online at [www.tripplite.com/en/products/model.cfm?txtModelID=4525](http://www.tripplite.com/en/products/model.cfm?txtModelID=4525).

Copyright © 2012 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.