

VGA over Cat5/6 Extender, Wall Plate Receiver for Video/Audio, Up to 1000 ft. (305 m), TAA

MODEL NUMBER: **B132-100A-WP-1**



Features

- Works with a local unit to extend a 1920 x 1440 (60Hz) Video and Audio signal up to 500 ft., or a 1024 x 768 (60Hz) Video and Audio signal up to 1,000 ft.
- 24Awg, Solid Wire Cat5e/6 cable, such as Tripp Lite's N022-01K-GY (Cat5) and N222-01K-GY (Cat6), is required to achieve maximum distance and resolution
- For optimal image quality between 500 and 1,000 ft., use Zero-Skew cable, such as Tripp Lite P524-01K
- Features built-in Equalization and Gain controls to adjust the video image
- RJ45 type wallplate allows you to use standard patch cable, eliminating the need for a 110 punchdown connection
- Ideal for digital signage situations, such as retail, schools, churches, etc..
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases
- 1 year limited warranty.

Highlights

- Works with a local unit to extend a 1920 x 1440 (60Hz) Video and Audio signal up to 500 ft., or a 1024 x 768 (60Hz) Video and Audio signal up to 1,000 ft.
- 24Awg, Solid Wire Cat5e/6 cable, such as Tripp Lite's N022-01K-GY (Cat5) and N222-01K-GY (Cat6), is required to achieve maximum distance and resolution
- For optimal image quality between 500 and 1,000 ft., use Zero-Skew cable, such as Tripp Lite P524-01K
- RJ45 type wallplate allows you to use standard patch cable, eliminating the need for a 110 punchdown connection
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

System Requirements

Package Includes

- Extender remote (Receiver) wallplate
- Mini-Screwdriver for EQ/Gain adjustment
- Wallplate screws
- External Power Supply with NEMA 1-15P Plug (Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 2A, 5 ft.)
- Owner's Manual



Specifications

| OVERVIEW | |
|---|--|
| UPC Code | 037332160096 |
| Product Type | Receiver |
| AC Adapter | Input: 100-240V, 50/60Hz, 0.5A; Output: 5V, 2A, 5 ft. |
| Technology | VGA/SVGA; Stereo Audio; Cat5/5e; Cat6 |
| VIDEO | |
| Max Supported Video Resolution | 1920x1440 @ 60Hz |
| Max 720P Range (ft) | 500 |
| Max 1080P Range (ft) | 500 |
| Max 1280 x 720 (720p) Range (ft) | 500 |
| Max 1920 x 1080 (1080p) Range (ft) | 500 |
| Max 1920 x 1200 Range (ft) | 500 |
| Receiver/Transceiver Video Output | VGA |
| Receiver - Number of Video Outputs | 1 |
| Signal Range (ft) | 1000ft @ 1024 x 768 (60Hz) 500ft @ 1920 x 1440 (60Hz) |
| Signal Range (m) | 304.8m @ 1024 x 768 (60Hz) 152.4m @ 1920 x 1440 (60Hz) |
| Recommended Cabling | Solid Wire Cat6 Cables (Tripp Lite's N202-Series) |
| AUDIO | |
| Audio Output | 3.5mm |
| Audio Specification | Stereo Audio |
| POWER | |
| Power Source | Unit (Included) |
| Power Source Type | AC Adapter |
| AC Plug Type | NEMA 1-15P |
| External Power Supply Input Specs (V / Hz / A) | 100-240V / 50-60Hz / 0.5A |
| External Power Supply Output Specs (V / A) | 5V/2A |
| External Power Supply Cord Length (ft.) | 4.5 |
| External Power Supply Cord Length (m.) | 1.38 |
| External Power Supply DC Barrel Connector Specs | OD: 5.5 x 2.1 x 7.5mm, Positive Pin, Negative Sleeve |



| | |
|--|--|
| External Power Supply Certifications | FCC; PSE; TUV; UL; cUL |
| USER INTERFACE, ALERTS & CONTROLS | |
| LED Indicators | RJ45: Green (Connection), Orange (Data Transmission) |
| PHYSICAL | |
| Color | White |
| Number of Displays | 1 |
| Form Factor/Mounting Options | Wallplate |
| Shipping Dimensions (hwd / cm) | 18.29 x 16.51 x 5.59 |
| Shipping Dimensions (hwd / in.) | 7.20 x 6.50 x 2.20 |
| Shipping Weight (kg) | 0.41 |
| Shipping Weight (lbs.) | 0.90 |
| Unit Dimensions (hwd / cm) | 11.43 x 6.99 x 2.54 |
| Unit Dimensions (hwd / in.) | 4.5 x 2.75 x 1 |
| Unit Packaging Type | Box |
| Unit Weight (kg) | 0.23 |
| Unit Weight (lbs.) | 0.5 |
| Housing | Plastic |
| ENVIRONMENTAL | |
| Operating Temperature Range | 32 to 122 F (0 to 50 C) |
| Storage Temperature Range | -4 to 158 (-20 to 70 C) |
| Relative Humidity | 10% to 90% RH, Non-Condensing |
| COMMUNICATIONS | |
| Max 1024 x 768 Range (ft) | 1000 |
| Max 480P Range (ft) | 1000 |
| Max 1440 x 900 Range (ft) | 500 |
| Max 1080i Range (ft) | 500 |
| Max 1920 x 1440 Range (ft) | 500 |
| Max 480i Range (ft) | 1000 |
| Max 640 x 480 Range (ft) | 1000 |
| Max 800 x 600 Range (ft) | 1000 |
| Max 1600 x 1200 Range (ft) | 500 |
| EDID Compatible | Yes |
| USB Extension Support | No |



| CONNECTIONS | |
|--------------------------------------|----------------------------|
| Ports | 1 |
| Side A - Connector 1 | RJ45 (FEMALE) |
| Side B - Connector 1 | HD15 (FEMALE) |
| Side B - Connector 2 | 3.5MM (FEMALE) |
| FEATURES & SPECIFICATIONS | |
| Driver Required | No |
| Built-In Equalizer | Yes |
| STANDARDS & COMPLIANCE | |
| Certifications | Tested to FCC, RoHS, REACH |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 1-year limited warranty |

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>