

## SmartPro 208V 5kVA 3.75kW Line-Interactive Sine Wave UPS, 3U Rack/Tower, Network Card Options, USB, DB9 Serial

MODEL NUMBER: **SMART5000TEL3U**



### Description

Tripp Lite's SMART5000TEL3U intelligent, line interactive UPS protects server, networking and telecommunications equipment from blackouts, voltage fluctuations and surges in a compact rackmount housing. Completely self-contained UPS system occupies only 3 rack spaces (3U) in a standard 19 inch rack, making this model one of the smallest 5kVA UPS systems available. Included accessories support mounting 4 post rack enclosures. Large capacity 5000 VA/3750 watt UPS system accepts raw AC input, adjusting output to regulated 208V levels. One pair of 120V outlets support up to 600VA monitors and other low voltage accessories. Includes slot for internal Network Management Card option. Includes USB and 2 DB9 monitoring ports for unattended shutdown, remote control and monitoring of UPS system and power data. Five outlets (two L6-20R, one L6-30R and two 5-15R) allow the connection of high current 20 and 30 amp 208V connectors and up to two 120V devices (max 600VA at 120V).

### Features

- Large 5000VA/3750-watt output capacity accommodates solitary large loads or multiple low-power loads
- High power density 5kVA power module occupies only 3 rack spaces (3U)
- 16 minutes half-load runtime (with a continuous load 2500VA; much longer runtime available at smaller loads)
- Line-interactive voltage regulation corrects severe brownouts and overvoltages without using battery power
- High voltage output supports 208V server, internetworking and telecom applications
- Pair of 120V outlets supports up to 600VA for standard 120V monitors, voicemail and other low-power networking devices
- Five total outlets (two L6-20R, one L6-30R and two 5-15R)
- Diagnostic LEDs provide visual indication of 17 separate performance conditions
- USB & Serial ports enable data-saving unattended shutdown when used with Tripp Lite's PowerAlert

### Highlights

- 5kVA / 5000VA line interactive 3U rack/tower UPS; Sine wave output
- 208V nominal output during inputs of 174-282V; Supports 600VA 120V output
- USB, Serial, EPO & slot for Network Management Card options
- 97% line-mode efficiency; Hot-swappable internal batteries; Energy Star Compliant
- NEMA L6-30P input; 2 NEMA 5-15R, 2 L6-20R & 1 L6-30R outlets

### Package Includes

- SMART5000TEL3U UPS System
- USB & DB9 Serial cabling
- Mounting hardware
- Instruction manual



software, available via FREE download from [www.tripplite.com/poweralert](http://www.tripplite.com/poweralert)

- Built-in USB, DB9 RS-232 and DB9 contact closure communications ports for remote monitoring and unattended shutdown
- Compatible with Tripp Lite UPS management card options TLNETCARD, WEBCARDLX and SNMPWEBCARD
- Emergency Power Off (EPO) interface for emergency shutoff in large facilities
- Hot-swappable/user-replaceable batteries allow on-site battery replacement through the front panel without powering off connected equipment or removing the UPS from the rack
- Intelligent battery management system extends battery life
- UPS ships fully assembled and ready for installation; no time-consuming user battery connections required

## Specifications

OVERVIEW	
UPC Code	037332116116
UPS Type	Line-Interactive
INPUT	
Rated input current (Maximum Load)	24A
Nominal Input Voltage(s) Supported	208V AC
UPS Input Connection Type	L6-30P
UPS Input Cord Length (ft.)	10
UPS Input Cord Length (m)	3.1
Recommended Electrical Service	30A 208V
Input Phase	Single-Phase
OUTPUT	
Output Volt Amp Capacity (VA)	5000
Output kVA Capacity (kVA)	5
Output Watt Capacity (Watts)	3750
Output kW Capacity (kW)	3.75
Output Capacity Details	120V 5-15R outlets are limited to 450 watts (max.)
Power Factor	0.75
Nominal Voltage Details	120V output is limited to 450 watts
Frequency Compatibility	60 Hz



Output Voltage Regulation (Line Mode)	208 & 120V (-6%, +20%)
Output Voltage Regulation (Battery Mode)	+/- 5%
Output Circuit Breakers	20A double pole breaker supports L6-20R outlets, 5A breaker supports 5-15R outlets, L6-30R outlet is unbrokened
Output AC Waveform (AC Mode)	Sine wave
Output AC Waveform (Battery Mode)	Pure Sine wave
Nominal Output Voltage(s) Supported	208V
Output Receptacles	(2) 5-15R; (2) L6-20R; (1) L6-30R
Individually Controllable Load Banks	No
<b>BATTERY</b>	
Battery Type	Valve Regulated Lead Acid (VRLA)
Full Load Runtime (min.)	8.5 min. (3750w)
Half Load Runtime (min.)	20 min. (1875w)
Expandable Runtime	No
DC System Voltage (VDC)	48
Battery Recharge Rate (Included Batteries)	Less than 4 hours from 10% to 90% (typical, full load discharge)
Battery Access	Front panel battery access door
Internal UPS Replacement Battery Cartridge	&nbsp;<a class="productLink" href="//www.tripplite.com/3U-UPS-Replacement-48VDC-Battery-Cartridge-select-Tripp-Lite-SmartPro-UPS-RBC94-3U">RBC94-3U</a>&nbsp;  (quantity 3)
Battery Replacement Description	Hot-swappable, user replaceable batteries
<b>VOLTAGE REGULATION</b>	
Voltage Regulation Description	Automatic voltage regulation (AVR) maintains line power operation with an input voltage range of 167 to 260
Overvoltage Correction	Input voltages between 228V and 260V are reduced by 12%
Undervoltage Correction	Input voltages between 167V and 194V are boosted by 12%
<b>USER INTERFACE, ALERTS &amp; CONTROLS</b>	
Switches	2 Switches control off/on power status and alarm-cancel/self-test operation
Alarm Cancel Operation	Power-fail alarm can be silenced using alarm-cancel switch; once silenced, alarm will re-sound to indicate low-battery status
Audible Alarm	Audible alarm indicates power-failure, overload and low-battery conditions
LED Indicators	5 LEDs indicate line power, battery power, overload, voltage regulation and battery low/replace status
<b>SURGE / NOISE SUPPRESSION</b>	
UPS AC Suppression Joule Rating	1020



**Tripp Lite**  
 1111 W. 35th Street  
 Chicago, IL 60609 USA  
 Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

UPS AC Suppression Response Time	Instantaneous
EMI / RFI AC Noise Suppression	Yes
<b>PHYSICAL</b>	
Cooling Method	Fan
Installation Form Factors Supported with Included Accessories	4 post 19 inch rackmount
Installation Form Factors Supported with Optional Accessories	2 post rackmount ( <a href="http://www.tripplite.com/2-Post-Rack-Mount-Installation-Kit-3U-Larger-UPS-Transformer-Battery-Pack-Components-2POSTRMKITHD">2-Post-Rack-Mount-Installation-Kit-3U-Larger-UPS-Transformer-Battery-Pack-Components-2POSTRMKITHD</a> ); Tower ( <a href="http://www.tripplite.com/2U-9U-Tower-Stand-Kit-select-Rack-Mount-UPS-Systems-2-9USTAND">2U-9U-Tower-Stand-Kit-select-Rack-Mount-UPS-Systems-2-9USTAND</a> )
Minimum Required Rack Depth (cm)	76.20
Minimum Required Rack Depth (inches)	30
Primary Form Factor	Rackmount
Primary UPS Depth (mm)	635
Primary UPS Height (mm)	133
Primary UPS Width (mm)	445
Rack Height	3U
Shipping Dimensions (hwd / cm)	30.48 x 58.42 x 83.82
Shipping Dimensions (hwd / in.)	12.00 x 23.00 x 33.00
Shipping Weight (kg)	82.55
Shipping Weight (lbs.)	182.00
UPS Housing Material	Steel
UPS Power Module Dimensions (hwd, cm)	13.34 x 44.45 x 63.50
UPS Power Module Dimensions (hwd, in.)	5.25 x 17.5 x 25
UPS Power Module Weight (kg)	65.00
UPS Power Module Weight (lbs.)	143.3
<b>ENVIRONMENTAL</b>	
Operating Temperature Range	+32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius
Storage Temperature Range	+5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius
Relative Humidity	0 to 95%, non-condensing
AC Mode BTU / Hr. (Full Load)	366
Battery Mode BTU / Hr. (Full Load)	1423
AC Mode Efficiency Rating (100% Load)	97%
Audible Noise	45 dBA maximum, front side 1m



<b>COMMUNICATIONS</b>	
Network Management Cards	<a href="#">SNMPWEBCARD</a> & <a href="#">TLNETCARD</a> & <a href="#">WEBCARDLX</a>
Network Monitoring Port Description	Supports detailed monitoring of UPS and site power conditions
PowerAlert Software	For local monitoring via the UPS's built-in communication ports, download PowerAlert Local software at <a href="https://www.tripplite.com/poweralert">https://www.tripplite.com/poweralert</a>
Communications Cable	USB and DB9 cabling included
WatchDog Compatibility	Supports Watchdog application, OS and hard-reboot restart options for remote applications
Communications Interface	Contact closure; DB9 Serial; EPO (emergency power off); Slot for SNMP/Web interface; USB
<b>LINE / BATTERY TRANSFER</b>	
Transfer Time	7 milliseconds (AC to Battery), 1 millisecond (Battery to AC)
Low Voltage Transfer to Battery Power (Setpoint)	167
High Voltage Transfer to Battery Power (Setpoint)	260
<b>SPECIAL FEATURES</b>	
Grounding Lug	Back panel grounding lug
Cold Start (Startup in Battery Mode During a Power Failure)	Cold-start operation supported
High Availability UPS Features	Auto Probe Monitoring (requires WEBCARDLX); Automatic Voltage Regulation (AVR); Hot swappable batteries; Remote management; Sine wave output; Surge/noise protection
Green Energy-Saving Features	Greater than 95% efficiency - GREEN UPS
<b>STANDARDS &amp; COMPLIANCE</b>	
UPS Certifications	ENERGY STAR Qualified; Meets FCC Part 15 Category A (EMI); Tested to CSA (Canada); Tested to UL1778 (USA)
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	2-year warranty, 3 year with registration. Note: <a href="#">Registration is required</a> for 3-year warranty.
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$250,000 <a href="#">Ultimate Lifetime Insurance</a>

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>