





# Up/Down-Angle Cat6 Gigabit Molded Slim UTP Ethernet Cable (RJ45 Up-Angle M to RJ45 Down-Angle M), Blue, 1 ft.

MODEL NUMBER: N204-S01-BL-UD











Cat6 cable connects Gigabit Ethernet network components like routers, servers and switches in highdensity data centers.

#### **Features**

**Up-** and **Down-Angle Cat6** Ethernet Cable Connects Equipment in Data Centers and VoIP Networks This Cat6 cable is ideal for connecting network components, such as printers, computers, copiers, routers, servers, modems and switches, in hard-to-reach areas of space-constrained high-density data centers. Designed for fast transmission and excellent signal quality, this RJ45 patch cable ensures data transfer speeds up to 1 Gbps throughout your Gigabit Ethernet or VoIP network.

#### Special Slim Design for Better Airflow and Easier Installation in Crowded Racks

This Cat6 UTP patch cord is more than 38% smaller in diameter than standard Cat6a cable. This increases airflow in tight spaces, which helps keep your equipment cool and properly functioning. It also cuts down on clutter in crowded racks and patch panels, and makes the cable easier to install around corners and through cable management panels.

### Up- and Down-Angle RJ45 Patch Cable Makes Connecting and Disconnecting Easier

Both RJ45 male connectors are designed at 90-degree angles: one upward, the other downward. This helps prevent excessive bending and reduces stress on the cable. This space-saving cable is easy to plug into patch panels, switches and other devices located in a confined area or behind a desk.

# Blue Jacket to Avoid Misidentification That Can Cause Costly Downtime

This up/down-angle Cat6 Ethernet cable features a blue PVC jacket and molded blue ends. The blue color allows easy, fast identification in a crowded rack or workstation and helps prevent the cable from becoming inadvertently disconnected.

# **Highlights**

- Cat6 Ethernet patch cable delivers fast transmission speeds up to 1 Gbps in your

  LAN
- Up-angle and down-angle RJ45 ends are easy to plug into devices pressed against a wall
- Over 38% slimmer than standard Cat6 cables to increase airflow in full racks
- Easy to route around corners and through crowded cable management panels
- Cable is blue for fast, easy identification in a crowded rack or workstation

### **Applications**

- Build a Gigabit Ethernet or VoIP network through the connection of routers, modems, switches and servers in a high-density data center
- Connect a workstation computer to the company server to gain access to printers, scanners and copiers
- Combine with other Tripp Lite patch cables to set up a colorcoded system in a crowded rack
- Create a connection in a tight space, such as a repurposed server room or behind furniture

# **Package Includes**

 N204-S01-BL-UD Up/Down-Angle Cat6 Gigabit Molded Slim UTP Patch Cable (M/M), Blue, 1



ft.

# **Specifications**

| -                           |                              |
|-----------------------------|------------------------------|
| OVERVIEW                    |                              |
| UPC Code                    | 037332252449                 |
| INPUT                       |                              |
| Cable Length (ft.)          | 1                            |
| Cable Length (m)            | 0.3                          |
| Cable Length (in.)          | 12                           |
| Cable Length (cm)           | 30.5                         |
| PHYSICAL                    |                              |
| Cable Jacket Rating         | CM                           |
| Cable Outer Diameter (OD)   | 4.0mm                        |
| Cable Shielding             | UTP                          |
| Color                       | Blue                         |
| Material of Construction    | PVC                          |
| Snagless Connector          | No                           |
| Wire Gauge (AWG)            | 28                           |
| Wire Type                   | Stranded                     |
| ENVIRONMENTAL               |                              |
| Operating Temperature Range | 14 to 122 F (-10 to 50 C)    |
| Storage Temperature Range   | 5 to 140 F (-15 to 60 C)     |
| Relative Humidity           | 0% to 90% RH, Non-Condensing |
| COMMUNICATIONS              |                              |
| Network Speed               | 1Gbps                        |
| CONNECTIONS                 |                              |
| Side A - Connector 1        | RJ45 (MALE) - DOWN ANGLE     |
| Side B - Connector 1        | RJ45 (MALE) - UP ANGLE       |
| Contact Plating             | Gold                         |



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

| FEATURES & SPECIFICATIONS              |                           |  |
|--|---------------------------|--|
| Technology                             | Cat5/5e; Cat6             |  |
|  |                           |  |
| CERTIFICATIONS                         |                           |  |
| Certifications                         | RoHS and REACH Compliant  |  |
|  |                           |  |
| WARRANTY                               |                           |  |
| Product Warranty Period<br>(Worldwide) | Lifetime limited warranty |  |

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>