



Cisco Serial Console Rollover Adapter (M/F) - RJ45 to RJ45, Shielded, Blue

MODEL NUMBER: N034-001-SH









Converts a standard Ethernet cable into a serial rollover cable for connecting to Cisco or other hardware that requires rolled cables.

Features

Rollover Console Adapter Converts a Straight-Through Ethernet Cable to a Rollover Cable

This Cisco serial console rollover adapter connects to the end of any standard RJ45 Ethernet cable and internally rolls the pins to convert the cable from straight through to rollover. This allows you to create a rollover connection between a computer terminal and the RJ45 console port on a Cisco modem, router, firewall, switch or other serial-based device without having to buy new cabling.

Color-Coded to Avoid Misidentification That Can Cause Costly Downtime

This Cisco console rollover adapter features blue PVC molding. The color-coding allows easy, fast identification in a crowded switch or router and helps prevent the cable from becoming inadvertently disconnected.

Highlights

- Connects to any standard RJ45
 patch cable to create a rollover
 connection
- Internally rolls the pins to convert straight-through cable to rollover cable
- Color-coded blue for fast, easy identification in a crowded switch or router
- Recommended for Cisco modems, routers, switches and other serial devices

Applications

- Connect devices like Cisco switches, routers or other hardware that require rolled cables to an Ethernet network
- Change ports on a network device from straight-through to Cisco rollover

System Requirements

- Cisco or other network hardware using RJ45 serial ports that requires rolled cables
- Standard Ethernet patch cable with RJ45 connectors

Package Includes

N034-001-SH Cisco Console
 Rollover Cable Adapter (M/F) RJ45 to RJ45, Shielded, Blue

Specifications

OVERVIEW	
UPC Code	037332253064





PHYSICAL		
Cable Jacket Type	PVC	
Cable Shielding	STP	
Color	Blue	
Unit Dimensions (hwd / cm)	1.88 x 2.05 x 5.25	
Unit Dimensions (hwd / in.)	0.74 x 0.81 x 2.07	
Unit Dimensions (hwd / mm)	18.8 x 20.5 x 52.5	
ENVIRONMENTAL		
Operating Temperature Range	14 ~ 122°F (-10 ~ 50°C)	
Storage Temperature Range	5 ~ 140°F (-15 ~ 60°C)	
Relative Humidity	0% ~ 90%, Non-Condensing	
CONNECTIONS		
Side A - Connector 1	RJ45 (MALE)	
Side B - Connector 1	RJ45 (FEMALE)	
FEATURES & SPECIFICATIONS		
Technology	Cat5/5e; Cat6	

© 2020 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies