

## 5-Port Unmanaged Industrial Ethernet Switch - 10/100 Mbps, Ruggedized, -40° to 75°C, DIN/Wall Mount

MODEL NUMBER: NFI-U05



Industrial-grade switch expands Ethernet connectivity to factory floors and other environments with space constraints and wide temperature ranges.

### Features

#### 5-Port Unmanaged Ethernet Switch Connects Your Devices to a LAN

This space-saving Tripp Lite switch transmits data over an Ethernet network. Five auto-negotiating 10/100 Mbps ports send data only to the devices designated to receive it, which improves the efficiency and potential throughput of the network.

#### Ruggedized Metal Housing Built to Last in Harsh Environments

The compact NFI-U05 adds 10/100 Mbps Ethernet capacity to your industrial and commercial applications, such as factory floors, warehouse operations and other environments with space constraints and wide temperature ranges. The industrial-grade high-strength case withstands vibration, shock and free fall. It can also operate in extreme temperatures ranging from -40 to 75 degrees Celsius (-40 to 167 degrees Fahrenheit).

#### Unmanaged Switch Requires Little to No Configuration

Quickly connect your network devices with little to no configuration. LEDs indicate when the switch is powered on and which Ethernet ports are showing activity. The NFI-U05 supports MAC address auto-learning and auto-aging for efficient routing, as well as automatic MDI/MDI-X crossover detection for plug-and-play functionality. IEEE 802.3x flow control allows smooth transmission of large files.

#### Flexible Mounting Options

The open-type device may be DIN mounted using the pre-installed rail clip, which mounts firmly to any standard 35 mm DIN rail. It may also be wall mounted using the rear mounting holes. A 3-pin 12–48VDC terminal block supplies power input. Device power must be supplied by SELV circuit.

#### TAA-Compliant for GSA Schedule Purchases

The NFI-U05 is compliant with the Federal Trade Agreements Act (TAA), which makes it eligible for GSA (General Services Administration) Schedule and other federal procurement contracts.

## Specifications

### Highlights

- 5 auto-negotiable 10/100 Mbps RJ45 ports connect devices over a LAN
- Industrial-grade switch supports operating temperature range of -40° to 75°C
- Easy-to-read LEDs indicate connection and activity status for all 5 Ethernet ports
- Plug-and-play operation with no software or configuration required before use
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

### Applications

Expand reliable Ethernet connectivity to factory floors and outdoor environments with space constraints and wide temperature ranges

### Package Includes

- NFI-U05 5-Port Unmanaged Industrial Switch
- DIN rail-mounting clip (pre-installed)
- Owner's manual



<b>OVERVIEW</b>	
UPC Code	037332264268
<b>INPUT</b>	
Maximum Input Amps Details	Maximum of 0.15A DC. The device power shall be supplied by SELV circuit
Voltage Compatibility (VDC)	From 12~48
Power Source	3-Pin Terminal Block
<b>USER INTERFACE, ALERTS &amp; CONTROLS</b>	
LED Indicators	1- PWR(Green): for Power; 2- 100(Green): for Ethernet speed 100Mbps; 3- LNK/ACT(Green): for data transmitting/receiving
<b>PHYSICAL</b>	
Primary Form Factor	Din-Rail; Wall-mount
Color	Black
Material of Construction	Aluminum casing
Shipping Dimensions (hwd / in.)	2.44 x 5.04 x 9.33
Shipping Weight (kg)	0.31
Unit Dimensions (hwd / in.)	4.3 x 0.9 x 2.9
Unit Weight (kg)	0.19
Unit Weight (lbs.)	0.42
<b>ENVIRONMENTAL</b>	
Storage Temperature Range	-40°F to 185°F (-40°C to 85°C)
Relative Humidity	5% to 95% (Non-Condensing)
Operating Temperature	-40°F to 167°F (-40°C to 75°C)
Power Consumption (Watts)	3.00
<b>COMMUNICATIONS</b>	
Network Compatibility	100 Mbps (Fast Ethernet)
Network Compatibility Details	Auto-negotiable
Switching Capacity	1Gbps
Switching Capacity Details	200Mbps Per Port with Full Duplex
<b>CONNECTIONS</b>	
RJ45 Ports	5
RJ45 Ports Detail	5x 10/100Base-T



SFP Uplink Ports	0
PoE Supported Ports	0
Network Switch Ports	(5) 10/100 (RJ45)
<b>FEATURES &amp; SPECIFICATIONS</b>	
Jumbo Frames	0
Console Port	No
MAC Auto Learning	Yes
RMON	No
SNMP	No
Storm Control	No
DHCP Snooping	No
Auto MDI/MDIX Crossover Detection	Yes
<b>STANDARDS &amp; COMPLIANCE</b>	
Certifications	Compliant Standards: IEEE 802.3 10Base-T; IEEE 802.3u 100Base-TX; IEEE 802.3x Flow control; IEEE 802.3 Auto-Negotiation
Approvals	FCC, CE, RoHS, REACH
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	3-year limited warranty

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <https://www.tripplite.com/products/product-certification-agencies>