


100G Duplex Multimode 50/125 OM4 Armored Fiber Optic Cable (LC/LC Duplex M/M), LSZH, Aqua, 15 m (49.2 ft.)

MODEL NUMBER: N821-15M-AQ-AR







100 GbE Ethernet cable with protective steel armor supports high bandwidths necessary for cloud services, hyperscale data centers and telecom carriers.

Features

100 GbE Cable Supports Higher Bandwidths Needed for Data Networking

As the amount of traffic in data networks grows, so does the need for devices and fiber cables to support higher bandwidths in cloud services, hyperscale data centers, telecom applications and equipment OEM companies. This duplex multimode 50/125 OM4 cable is an ideal choice for 100G Ethernet applications up to 15 meters (49.2 feet) at 850 nm. It is also backward compatible with 10 Gb, 25 Gb and 40 Gb networks, so you can future-proof your current application for an eventual upgrade to 100 Gb.

Armored Cable Provides Great Flexibility and Durability

The N821-15M-AQ-AR can be run anywhere and does not need to be in conduit. Built-in flexible stainless steel and robust Aramid yarn protect the optical fibers more effectively than standard fiber optic cables do. The rugged armored tubing allows optical fiber to be installed in the most hazardous areas, including environments with excessive dust, oil, gas and moisture. This fiber cable provides low insertion loss and high return loss.

Aqua Jacket Helps Avoid Misidentification That Can Cause Costly Downtime

The OM4-rated cable has an aqua-colored jacket to identify it as multimode in a crowded patch panel or switch and prevent it from becoming accidentally disconnected. The round low-smoke zero-halogen (LSZH) jacket limits the amount of toxic smoke emitted in case of combustion, making it suitable for poorly ventilated areas.

Specifications

OVERVIEW UPC Code 037332265715 Technology Multimode

Highlights

- OM4-rated cable recommended for 100 Gb speeds up to 15 meters (@ 850 nm)
- Flexible stainless steel tubing protects fiber and helps cable stand up to rigorous use
- Backward compatible with 10/25/40 Gb networks to facilitate future-proofing
- Aqua LSZH jacket allows fast, easy identification in a crowded switch or patch panel

Applications

Connect 100G fiber Ethernet networks in your cloud service, hyperscale data center or telecom application

Package Includes

N821-15M-AQ-AR 100Gb Duplex Multimode 50/125 OM4 Armored Fiber Optic Cable, Aqua, 15 m (49.2 ft.)



Tripp Lite 1111 W. 35th Street Chicago, IL 60609 USA Telephone: 773.869.1234 www.tripplite.com

| Optical Mode | OM4 | |
|------------------------------------|--|--|
| Mode Type | Multimode | |
| PHYSICAL | | |
| Color | Aqua; White | |
| Material of Construction | Outer Jacket: PVC (LSZH Rating); Inner Flexible Steel Tube: SUS204 (Armored) | |
| Cable Jacket Color | Aqua | |
| Cable Jacket Material | LSZH | |
| Cable Jacket Rating | OFNR | |
| Cable Outer Diameter (OD) | 3.0MM | |
| Clad Diameter (microns) | 125 | |
| Core Diameter (microns) | 50 | |
| Primary Coating Diameter (microns) | 550 | |
| Number of Fibers | 2 | |
| Cable Length (ft.) | 49.2 | |
| Cable Length (m) | 15.00 | |
| Cable Length (in.) | 590.6 | |
| Minimum Bend Radius | 30mm | |
| Shipping Dimensions (hwd / in.) | 9.00 x 7.00 x 0.50 | |
| Shipping Weight (kg) | 0.22 | |
| ENVIRONMENTAL | | |
| Operating Temperature Range | -4 to 140 °F (-20 to 60 °C) | |
| Storage Temperature Range | -4 to 140 °F (-20 to 60 °C) | |
| Operating Humidity Range | 5% to 85% RH, Non-Condensing | |
| Storage Humidity Range | 5% to 85% RH, Non-Condensing | |
| COMMUNICATIONS | | |
| Network Compatibility | 10 Gbps; 25 Gbps; 40 Gbps; 100 Gbps | |
| Wavelength | 1300nm; 850nm | |
| Attenuation @ 850NM | 3.0dB/Km | |
| Attenuation @ 1300NM | 1.0dB/KM | |
| Insertion Loss | 0.20dB | |
| CONNECTIONS | | |
| Side A - Connector 1 | LC DUPLEX (MALE) | |
| Side B - Connector 1 | LC DUPLEX (MALE) | |



| Endface Polish | PC | |
|--|---------------------------|--|
| Connector Color | Aqua; White | |
| | | |
| FEATURES & SPECIFICATIONS | | |
| Push/Pull Tabs | No | |
| Optical Port | LC | |
| Breakout | No | |
| Trunk | No | |
| Armored Cable | Yes | |
| | | |
| STANDARDS & COMPLIANCE | | |
| Certifications | RoHS, REACH | |
| Approvals | RoHS, REACH | |
| | | |
| WARRANTY | | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty | |

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies