

# Safe-IT Antibacterial Hospital-Grade Extension Cord, 5-15P to 5-15R - Green Dot, 13A, 125V, 16 AWG, Black, 15 ft. (4.6 m)

MODEL NUMBER: P022AB-015-HG











Hospital-grade extension cord with antibacterial properties connects two devices with 5-15P-HG/5-15R-HG power connectors in a hospital, lab or clinic.

#### **Features**

#### Hospital-Grade Extension Cord is a Safe Solution for Medical Facilities

This Safe-IT™ hospital-grade power cord is designed for computers, mobile carts, printers, scanners, monitors and other compatible hospital equipment within a healthcare facility. It features a NEMA 5-15R-HG end for connecting to a device and a NEMA 5-15P-HG plug for connecting to a hospital-grade AC power source located outside patient care vicinities. The 15-foot (4.6-meter) length allows you great flexibility in placing equipment with respect to the power outlet.

### **Provides Extra Protection Against Certain Bacteria**

The connectors and PVC jacket are constructed using an antibacterial material that is effective in inhibiting the growth of Escherichia coli (E. coli) and Staphylococcus aureus (staph). This added protection makes this cable an ideal solution for medical environments, such as hospitals, laboratories and clinics, and anywhere else that needs extra protection against bacteria.

#### **Designed and Tested to Strict Hospital-Grade Standards**

This cord is tested to ANSI/UL 62 and 817 standards, as well as CAN/CSA C22.2 no. 21 and 49 standards, ensuring it's a dependable power solution for hospital environments.

# **Specifications**

OVERVIEW	
UPC Code	037332266156
Device Compatibility	Mobile Cart; Computer; Printer; Monitor/HDTV; Server; UPS; PDU
Country/Region	North America

# **Highlights**

- Recommended for connecting devices to power outlets outside patient care vicinities
- Made with antibacterial material proven effective in inhibiting the growth of E. coli and staph
- Adds 15 ft. to your existing power connection to allow great flexibility in placing devices
- 5-15P-HG plug connects to AC power; 5-15R-HG end connects to device's input cord
- Tested to ANSI/UL 62 and 817 and CAN/CSA C22.2 no. 21 and 49 standards

# **Package Includes**

P022AB-015-HG Antibacterial Hospital-Grade Extension Cord, 5-15P to 5-15R, Black, 15 ft. (4.6 m)



Maximum Input Amps	13
Voltage Compatibility (VAC)	125
voltago compatibility (vito)	
PHYSICAL	
Plug Color	Black
Cable Jacket Color	Black
Connector Color	Black
Cable Jacket Material	PVC
Cable Jacket Rating	FT2
Power Cord Jacket Type	SJT
Cable Outer Diameter (OD)	0.325"
Number of Conductors	3
Wire Gauge (AWG)	16
Wire Gauge (OD - mm²)	1.31
Cable Length (ft.)	15
Cable Length (m)	4.57
ENVIRONMENTAL	
Operating Temperature Range	-4 to 140 F (-20 to 60 C)
Storage Temperature Range	-4 to 140 F (-20 to 60 C)
	2007 TO 2007 DIL No. Occalestics
Operating Humidity Range	20% TO 80% RH, Non-Condensing
Operating Humidity Range Storage Humidity Range	20% TO 80% RH, Non-Condensing 20% TO 80% RH, Non-Condensing
Storage Humidity Range	
Storage Humidity Range  CONNECTIONS  Side A - Connector 1	20% TO 80% RH, Non-Condensing
CONNECTIONS Side A - Connector 1 Side B - Connector 1	20% TO 80% RH, Non-Condensing  NEMA 5-15P  NEMA 5-15R
Storage Humidity Range  CONNECTIONS  Side A - Connector 1  Side B - Connector 1  FEATURES & SPECIFICATIONS	20% TO 80% RH, Non-Condensing  NEMA 5-15P  NEMA 5-15R
CONNECTIONS Side A - Connector 1 Side B - Connector 1 FEATURES & SPECIFICATIONS High Voltage	20% TO 80% RH, Non-Condensing  NEMA 5-15P  NEMA 5-15R  No
Storage Humidity Range  CONNECTIONS  Side A - Connector 1  Side B - Connector 1  FEATURES & SPECIFICATIONS  High Voltage  Locking Plug	20% TO 80% RH, Non-Condensing
CONNECTIONS Side A - Connector 1 Side B - Connector 1	20% TO 80% RH, Non-Condensing  NEMA 5-15P  NEMA 5-15R  No



Tripp Lite
1111 W. 35th Street
Chicago, IL 60609 USA
Telephone: 773.869.1234
www.tripplite.com

Certifications	UL/cUL, RoHS, REACH	
Approvals	UL/CSA	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2021 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>