

DC Power Supply for Tripp Lite N785-CH12 Media Converter Chassis, 75W

MODEL NUMBER: N785-CH75W-DC











Highlights

- Supplies DC power to a media converter installation using Tripp Lite's N785-CH12
- Multiple power supplies provide primary and redundant power to prevent downtime

System Requirements

Tripp Lite N785-CH12 Media Converter Chassis

Package Includes

N785-CH75W-DC 75W DC Power Supply

75W DC power supply provides primary or redundant power to your media converter installation.

Features

Powers Your Tripp Lite N785-CH12 12-Port Media Converter Chassis

This 75-watt DC power supply works with the Tripp Lite N785-CH12 media converter chassis to provide primary or redundant power. The N785-CH12 comes with a pre-installed AC power supply, but you can swap it out for the N785-CH75W-DC if you prefer DC power. This DC power supply can be used with any DC power source up to 48V 3A. A second DC power supply is also recommended to provide redundant power that helps prevent unwanted and expensive downtime. **Note**: Only one type of power supply should be used with the N785-CH12. Do not mix DC and AC power supplies.

Specifications

| OVERVIEW | | |
|--|------------------------|--|
| UPC Code | 037332267078 | |
| Accessory Type | Power Supply | |
| Accessory Class | Networking Accessories | |
| POWER | | |
| External Power Supply Input Specs (V / Hz / A) | 48V / 3A | |
| External Power Supply Output Specs (V / A) | 12V/6.5A | |
| External Power Supply Cord Length (ft.) | 6 | |
| External Power Supply Cord Length (m.) | 1.83 | |





| External Power Supply Plug(s) | NEMA 5-15P North America | |
|--------------------------------------|--------------------------|--|
| PHYSICAL | | |
| PHYSICAL | | |
| Power Cord Color | Black | |
| Unit Dimensions (hwd / in.) | 5.24 x 2.32 x 9.06 | |
| Unit Dimensions (hwd / cm) | 13.3 x 5.9 x 23.0 | |
| Unit Packaging Type | Вох | |
| | | |
| ENVIRONMENTAL | | |
| Operating Temperature Range | 32 to 122F (0 to 50C) | |
| Storage Temperature Range | 14 to 158F (-10 to 70C) | |
| Operating Humidity Range | 10% to 90% | |
| Storage Humidity Range | 5% to 95% | |
| | | |
| FEATURES & SPECIFICATIONS | | |
| Auto MDIX Support | No | |
| | | |
| STANDARDS & COMPLIANCE | | |
| Certifications | CE, FCC, RoHS, REACH | |
| External Power Supply Certifications | CE; FCC; RoHS | |
| | | |
| WARRANTY | | |
| Product Warranty Period (Worldwide) | 3-year limited warranty | |

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: https://www.tripplite.com/products/product-certification-agencies