

# Single-Gang European-Style Gang Frame for Insert Modules, White

MODEL NUMBER: N042E-WF1







## **Highlights**

- Ideal for home theater, VoIP or Ethernet in-wall wiring installations
- Helps prevent accidental cable damage and hides unattractive wiring
- Compatible with Tripp Lite N042E-Series European modules and inserts
- High-impact plastic construction designed to blend in with your home/office décor

### Package Includes

N042E-WF1 Single-Gang Europe-Style Gang Frame, White

European-style gang frame accepts compatible inserts for terminating premise audio/video, voice or data applications.

#### **Features**

#### European Gang Frame Connects Your In-Wall Audio/Video, Voice or Data Cable Line

This European-style outlet gang frame for mounting and trunking is ideal for terminating your premise wiring applications, including home theater, VoIP phones and Ethernet. The N042E-WF1 protects electrical and network cables to help prevent accidental damage to your application. It's compatible with Tripp Lite's N042E-Series European unloaded modules and blank insert (sold separately).

#### High-Impact Construction Designed to Blend In Seamlessly with Your Room

This white plastic cover plate measures 81 x 81 x 15 millimeters (outer frame) and 45 x 45 millimeters (inner frame). It helps hide unattractive cabling and blends elegantly into any home or office décor for a sleek, professional installation. The ABS plastic construction meets UL 94V-0 flame-retardant standards for protection against fire and high heat.

# **Specifications**

OVERVIEW	
UPC Code	037332268853
Accessory Type	Wall Plate
Technology	Cat5/5e; Cat6; Cat6a; DisplayPort; HDBaseT; HDMI; USB 2.0 (High Speed)
Country/Region	Europe
PHYSICAL	
Color	White
Material of Construction	ABS





Total Number of Ports	0	
Unit Dimensions (hwd / in.)	INNER: 1.77 X 1.77 X 0.59; OUTER: 3.19 X 3.19 X 1.77	
Finish	Matte	
ENVIRONMENTAL		
Operating Temperature Range	14 TO 140 F (-10 to 60 C)	
Storage Temperature Range	-40 TO 154.4 F (-40 to 68 C)	
Operating Humidity Range	10% TO 90% RH, (NON-CONDENSING)	
Storage Humidity Range	10% TO 90% RH, (NON-CONDENSING)	
FEATURES & SPECIFICATIONS		
Snagless Connector	No	
Antibacterial	No	
STANDARDS & COMPLIANCE		
Product Certifications	UL 94; UL Listed; cUL Listed	
Product Compliance	RoHS; REACH	
WARRANTY		
Product Warranty Period (Worldwide)	Lifetime limited warranty	

© 2022 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies: <a href="https://www.tripplite.com/products/product-certification-agencies">https://www.tripplite.com/products/product-certification-agencies</a>